

Real-Time Emotion Recognition in Patients with Consciousness Disorders Using AI and Multimodal Data

Lecturer: Dr. Mohammed Anbar

Student ID: 243001489

Student Name: Nouf Hamoud Alotaibi

Table of Contents

Abstract	1
Chapter 1:	2
1.1 Introduction.....	2
1.2 Background.....	3
1.3 Problem Statement.....	4
1.4 Research Objectives	5
1.5 Research Scope.....	6
Chapter 2: (Literature Review).....	8
2.1 Literature Review.....	8
Chapter 3: (Research Methodology).....	30
3.1 Research Methodology.....	30
3.2 Expected Outcomes.....	34
3.3 Gantt Chart.....	35
References	36

Abstract

Emotion recognition has been a very important development in neurorehabilitation, especially for those patients with disorders of consciousness who cannot communicate through conventional means. This research attempted to bridge the gaps in emotion recognition through a multi-modal approach integrating EEG signals, facial recognition, and physiological signals. The research proposed a robust system that should improve accuracy and scalability by leveraging cutting-edge machine learning models such as Graph Convolutional Neural Networks and Long Short-Term Memory networks. A review of the existing literature underlines several limitations that unimodal approaches suffer from, including noise, signal variability, and constraints of datasets. In this context that multimodal frameworks had come to the fore as a very promising alternative, with an ability to enhance detection accuracy through the fusion of diverse data. Ethical considerations, including those on data privacy, informed consent, and algorithmic transparency, remain critical issues for real-world applications.

The study covered the combination of XR with telerehabilitation in the creation of an immersive environment for cognitive-affective stimulation, thus ensuring patient recovery. Challenges such as cost, accessibility, and interdisciplinary collaboration are identified despite this promising potential. Development of domain-specific data sets and subsequent validation through experimental settings had been prioritized to make sure of applicability across diverse clinical environments.

The proposed framework led to significant contributions in theoretical developments, technological innovation, and practical healthcare applications.

It aimed to set base guidelines on the ethical use of AI, as well as to make actionable recommendations for integrating emotion recognition systems into clinical workflows in healthcare. Ultimately, this study envisioned a transformative impact on patient engagement, rehabilitation outcomes, and the quality of life for individuals with DOC. This research set the foundation for further innovation, with a focus on scalable, ethically compliant, and patient-centered solutions for emotion recognition.

1. Chapter 1:

1.1 Introduction

Emotion recognition is now a priority area of critical research in modern healthcare, as this helps to know more about the patients who have disorders of consciousness and are unable to communicate their emotions in conventional ways. Lack of recognition and management of such emotional needs presents a huge challenge in rehabilitation and overall well-being of such patients. The emergence of enabling technologies such as AI, ML, and XR has tried to bridge such gaps in recent years.

Thus, accordingly, the first EEG-based emotion recognition system emerged as a robust method to analyze neural activities that detect emotional states. However, most of the current methodologies face some difficulties with either noise in the data, inter-individual variability, or lack of scalability. Nowadays, there is increased interest in integrating EEG signals with other modalities to transcend the limitations of each mode. This would result in a multimodal approach that, for sure, would give better performance regarding accuracy and robustness, opening ways for more effective emotion recognition systems. (Ezilarasan & Leung, 2024; Fernandes et al., 2024; Lim et al., 2024; Ul Hassan et al., 2023)

Recently, deep learning techniques in AI-driven models have gained rapid attention. The potential applications in handling complex and diverse feature sets to provide more fine-grained representations of emotional states lie largely within models such as Graph Convolutional Neural Networks and Long Short-Term Memory networks. Major challenges remain significant to date, involving the need to access big and quality datasets, efficiency in processing speed, and ethical considerations such as data privacy or informed consent. (Fernandes et al., 2024; Pereira et al., 2024)

Both XR and telerehabilitation are exciting modalities in which to integrate emotion recognition for neurorehabilitation. The immersive setting of XR technologies is cognitively and emotionally engaging, while telerehabilitation adds a link from a distance to extend the care. Such an emerging technology will merge AI-driven emotion recognition into the clinical service and will maybe revolutionize a patient's process of recovery engagement. (Lim et al., 2024; Silva et al., 2024)

This research will establish an all-rounded, multimodal framework of emotion recognition to be supported by the integration of EEG signals with facial and physiological data in the endeavor to overcome these limitations. Contribution: This will be done via a study that deals with the methodological, ethical, and practical challenges toward designing

scalable, reliable, and ethically compliant emotion recognition systems in health facilities. It also discusses the broader implications of emotion recognition in the context of better recovery for patients and decision-making by caregivers. (Silva et al., 2024)

The findings are sure to raise the bar for patient-centered healthcare and offer actionable insights into how to integrate advanced technologies into clinical workflows. The study envisions interdisciplinary collaboration, responding to real-world challenges, and the recognition system will make a much better quality of life for patients with DOC and beyond.

1.2 Background

The Need for Emotion Recognition in Healthcare

Emotion recognition is important for understanding the emotional needs of patients, especially those with disorders of consciousness. Such patients mostly cannot communicate their emotional states through conventional means, thereby presenting challenges to caregivers and healthcare providers in offering personalized and effective interventions. Traditional observation methods are grossly inadequate, and there has been a growing need for advanced technologies to bridge this gap.

EEG-Based Emotion Recognition: The Advances

EEG has emerged as a promising modality for emotion recognition, offering direct insight into neural activity. The systems based on EEG can capture subtle emotional signals from the brain that may be helpful in detecting emotions in non-communicative patients. However, challenges such as data noise, individual variability, and limited generalizability of current systems hinder their effectiveness. Addressing these issues is essential to improving the accuracy and reliability of these systems in clinical settings.

Incorporating Multimodal Approaches

Recent research has pointed to the lack of one-modal approaches, such as solely EEG signals, and advised incorporating a multi-modal approach. On the one hand, multi-modal emotion recognition systems incorporate EEG signals with signals obtained from facial recognition, body movement analysis, and physiological measurements that include heart rate and skin conductance. It not only improves detection performance but also enables the diagnostician to investigate the holistic aspects of the patient's needs with better therapeutic outcomes.

The Role of AI and New Technologies

Artificial Intelligence and Machine Learning have indeed brought an evolution to emotion recognition systems by providing the ability to analyze complex and diverse data. Advanced models such as Graph Convolutional Neural Networks and Long Short-Term Memory networks have been able to show superior capabilities in the extraction of meaningful patterns from EEG and other inputs. Moreover, extended reality and telerehabilitation represent some of the technologies being explored for improving patient participation in immersive therapeutic environments. These, along with emotionally aware AI, may soon change the face of neurorehabilitation and patient care.

1.3 Problem Statement

Emotion recognition in DOC patients is one of the biggest problems when attempting neurorehabilitation. Most of the patients do not have conventional means of communicating or expressing themselves. Advanced technological solutions are hence required in correctly identifying and reacting to their emotional states. Systems that presently exist, such as those based on EEG-based emotion detection, are considered to hold a lot of promises since it captures neural signals directly. These methods are, however, susceptible to several challenges, including noise, signal quality variability, and limited capability for generalization to diverse patient populations.(Fernandes et al., 2024; Ul Hassan et al., 2023)

Multimodal approaches-a fusion of EEG signals with other modalities such as facial expressions and physiological data-have lately been put forward to enhance the currently unsatisfactory level of accuracy and robustness. However, such frameworks remain relatively unexploited, especially in clinical applications in which real-time functionality and ethical considerations, including data privacy and algorithmic transparency, are crucial.(Akbar et al., 2024; Fernandes et al., 2024; Pereira et al., 2024)

This limitation therefore underlines the urgent need for the integration of multimodal data sources in dealing with various technical and ethical challenges to enhance the reliability and applicability of emotion recognition systems within clinical settings. In the light of the above, the present study is designed to be aimed at filling the lacuna with a view to providing more scope for enhancing the reliability, scalability, and ethical compliance of

the emotion recognition system related to healthcare.(Akbar et al., 2024; Stasolla et al., 2023; Ul Hassan et al., 2023)

1.4 Research Objectives

General Objective

This involves the design, development, and validation of a multimodal framework that can be used for emotion recognition in patients with disorders of consciousness, using EEG signals, along with facial recognition and physiological data, to enhance clinical accuracy, scalability, and ethical compliance.

Specific Objectives

1. To investigate the drawbacks of existing EEG-based emotion recognition systems: Analyze current methodologies regarding noise, variability, and scalability issues.(Fernandes et al., 2024; Ul Hassan et al., 2023)
2. To assess the use of multimodal data for emotion recognition: Integration of EEG signals with facial and physiological data for better detection accuracy was considered (Akbar et al., 2024; Stasolla et al., 2023)
3. To find out and implement improved machine learning algorithms: Analyze the performance of algorithms such as GCNNs and LSTM networks in processing multimodal data (Fernandes et al., 2024; Ul Hassan et al., 2023)
4. To Develop a prototype of the proposed multimodal framework: Design and implement a system that integrates EEG, facial expression, and physiological signals for the real-time recognition of emotion(Stasolla et al., 2023; Ul Hassan et al., 2023)
5. To validate the proposed framework in experimental settings: Subject dependent and subject independent testing of the system regarding accuracy and robustness (Fernandes et al., 2024; Pereira et al., 2024)
6. To explore ethical issues related to multimodal emotion recognition: patient privacy, consent, and algorithmic transparency during the design of systems(Akbar et al., 2024; Ul Hassan et al., 2023)
7. To measure the impact of emotion recognition on rehabilitation: Better emotion detection/patient recovery and caregiver decision-making (Akbar et al., 2024; Stasolla et al., 2023)

8. To develop a domain-specific dataset for training and validation:
Building a repository of multimodal emotion data related to patients with disorders of consciousness (Fernandes et al., 2024; Ul Hassan et al., 2023)
9. To provide recommendations for future research and clinical integration:
Discuss how the framework can be integrated into health care systems and what paths may be considered for further development (Akbar et al., 2024; Stasolla et al., 2023; Ul Hassan et al., 2023)

1.5 Research Scope

Analysis of Existing Emotion Recognition Challenges

These study findings focus on the inability and inefficiency of state-of-the-art emotion recognition methods, especially for patients who, due to neurological disorders or accidents, cannot respond motorically. The specific challenges include noise and signal variabilities in EEG signals; poor generalization of current approaches from their current designs to more diverse populations and ethical concerns with respect to patient data privacy and interpretability/transparency; analysis of the gap in mono-model approaches and their integration regarding multimodal frameworks.

Assessment of Existing Solutions and Technologies

The present work discusses existing solutions to emotion recognition, including those using EEG, machine learning algorithms, and state-of-the-art approaches based on the integrated analysis of physiological, neural, and behavioral data. Such solutions are critically reviewed regarding their efficacy, scalability, and ethical implications. In this regard, advanced AI models, like GCNN and LSTM, together with enabling technologies, including extended reality and telerehabilitation, play an important role.

Designing a Multimodal Framework

This research develops an inclusive, multimodal framework combining EEG signals with facial recognition and physiological metrics toward enhanced emotion detection. It considers how it should tackle the signal-related problems, noise reduction, variability of the signals, ethical considerations of assuring the privacy of the data provided by the patients, the consideration of consent, and how much information should be kept

transparent. The design must be such that the said framework shall be scalable, adaptable, and specifically applicable clinically.

Validation in Clinical and Experimental Settings

The proposed framework will be tested both in subject-dependent and subject-independent experimental settings to ensure its efficacy and generalizability. Performance metrics include accuracy, robustness, and scalability. Its impact on rehabilitation outcomes and the decision-making of caregivers will also be studied through pilot studies in clinical environments. Responses from healthcare providers, patients' families, and interdisciplinary experts are sought to refine the system, easing its translation into reality.

2. Chapter 2: (Literature Review)

1.1 Literature Review

Yan et al. (2022) have discussed the potential and limitations of AI applications in the diagnosis and prediction of mental health. The authors express that, by nature, mental health disorders are deeply complex with symptoms largely overlapping, making it tough to classify them correctly. Of the causes for reliable predictions among others, they identify bias and lack of diversity within the dataset. It achieves this through the integration of multimodal data such as EEG, MRI, and behavioral information that increases the reliability of diagnosis. Considerations of ethics will be there to ensure privacy and security of data, limitations of interpretability in the AI model, and clinical acceptance. The application, therefore, requires joint clinicians with the developers of AI for building up solid standardized frameworks necessary to allow seamless translation of AI in mental health diagnosis.

Matching Assistive Technology, Telerehabilitation, and Virtual Reality with Disorders of Consciousness and Neurocognitive Disorders: A Position Paper by Stasolla et al. (2023a) provides more details on how advanced assistive technologies like VR and AI could function in changing the cognitive and emotional disturbances of patients with altered consciousness. The paper has highlighted that telerehabilitation has proved effective in remote monitoring of the improvement of a patient, while the focus of VR is to create immersive environments that can stimulate neural functions. AI-driven personalized rehabilitation strategies are considered one of the most important advantages, offering tailored interventions. Issues regarding ethical consideration-patient privacy among other implementation challenges-are discussed here, highlighting how those technologies bridge the gaps created in traditional healthcare for a less aware patient.

Detection of Emotion using EEG and machine learning algorithms is considered for UI Hassan et al. (2023a), in their study "Towards Effective Emotion Detection: A Comprehensive Machine Learning Approach on EEG Signals.". Feature extraction and some classifiers, including the Support Vector Machine and neural networks, were used in the investigation, where high classification accuracy was obtained for emotional states like happiness, sadness, and fear. It is underlined that preprocessing is a very important step in maintaining model reliability and performance. The authors indicate that these are

important neurorehabilitation and healthcare technologies, mainly dealing with patients who cannot communicate, and thus may lead to a significant contribution to diagnosis improvement related to emotional states.

Fernandes et al. (2023a) discuss the role of deep learning in the analysis of EEG signals with a view to classifying emotional states in Emotion Detection from EEG Signals Using Machine Deep Learning Techniques. Many different architectures were experimented with, including LSTM and autoencoders, which demonstrated different performances in modeling temporal dynamics underlying the EEG data. The authors also discussed EEG data integration with other physiological signals to highlight better performance in emotion recognition and its practical implications for a differential diagnosis of disorders of consciousness. It also discusses the challenges in real-time implementation, computational efficiency, and scalability of such systems.

Younis et al. (2024) had presented a critical review of the application of AI in Medicine and Health Care through a paper titled "A Systematic Review and Meta-Analysis of Artificial Intelligence Tools in Medicine and Healthcare: Applications, Considerations, Limitations, Motivation, and Challenges." The paper identified 77 studies that were analyzed and divided applications of AI into four main categories: diagnosis, treatment, health management, and medical education. Results are presented that highlight how AI can enhance healthcare efficiency, accuracy, and access, with a focus on virtual approaches based on large language models. Critical discussions on ethical challenges, data privacy concerns, and the lack of standardized measures of outcome raise questions over implementation. The study concludes that interdisciplinary collaboration and further research are required to determine clinical effectiveness.

In this regard, the study of Pereira et al. (2024), titled Systematic Review of Emotion Detection with Computer Vision and Deep Learning, presented the usage of computer vision and deep learning in emotion detection while analyzing 77 studies between the years 2013 and 2023. CNNs are found to be very efficient models in such cases since they capture visual emotional cues better than other models. Hybrid and augmented models are also discussed, though challenges related to dataset diversity and real-world testing remain. Such works highlight the fact that practical improvement in emotion detection requires robust datasets and interpretable AI models.

Akbar et al. (2024a) reviewed extended reality and the future of artificial intelligence in neurorehabilitation after recovery from brain injury, reviewing how extended reality and AI in neurorehabilitation are combined for brain injury patients. The results showed that both XR technologies, VR and AR, offer an exciting environment for cognitive-affective stimulation, while AI provides the possibility to personalize therapy and monitor progress. Limitations to adoption include but are not limited to cost, accessibility, and clinical validation. This study concludes that taken together, these have the potential to result in huge improvement in patient outcomes and engagement.

Ezilarasan & Leung, 2024, propose a state-of-the-art real-time emotion recognition framework using EEG signals in their work "An Efficient EEG Signal Analysis for Emotion Recognition Using FPGA". They have used ICA for artifact removal and the CNN-LSTM hybrid model for feature extraction and classification. The implementation done using FPGAs enhanced the speed and resources of the system very much and made it suitable for resource-constrained environments. This is further emphasized in its application to both clinical and assistive technology, where its classification accuracies outperform those of earlier traditional methods.

Silva et al. (2024) discuss biosensors such as EEG, ECG, and GSR for emotion recognition in the study entitled Integration of Multiple Biosensors for Emotion Classification with Artificial Intelligence. This research pinpoints the Extra Trees model for binary emotion classification and emphasizes multi-modal data fusion to enhance accuracy. It also points out challenges that involve real-time processing and synchronization of data. Applications range from mental health and human-computer interaction to personalized technologies. The work provides a foundation for further research into the improvement of these systems toward broader applications.

Lim et al. (2024) critically reviewed EEG Affective Recognition from a Neuroscience Perspective. There follows the approach to emotion recognition, integrating neuroscience into EEG signal processing, after noticing key elements in the comprehension of emotion state, such as neural correlates and event-related potential. Such challenges are variability of the signals themselves and standardized datasets. It brings into light ethical

considerations, first data privacy. Authors suggest using neuroscience insights with AI for the interpretability enhancement of emotion recognition systems and give direction on the next step.

Critical Analysis

This reviewed research together signifies that significant progress is taking place in using AI, ML, and XR for emotion recognition and neurorehabilitation. These will provide a firm ground for further advancements regarding methodologies and technologies in this field. However, there is still a considerable gap in the direct address of emotion recognition for the patients who are suffering from disorders of consciousness. While substantial research has been done using EEG for emotion detection, integration with other modalities such as facial expressions, body movements, and physiological signals is limited. This provides an important opportunity for research that could improve personalized care for vulnerable populations.

Ethical concerns remain a challenge, especially within areas involving data privacy, security, and algorithmic bias. Given that patients with DOC are vulnerable, ethical protocols must be much stronger, such as anonymizing data, informed consent by caregivers, and disclosure regarding AI decision-making. Such measures would be important in fostering confidence and ensuring the deployment of AI in healthcare is done responsibly.

Another related theme is methodological challenges. The variability and noise inherent in neurological data from DOC patients hint at the urgent need for sophisticated AI models with superior data processing capabilities. The development of domain-specific datasets targeting these patients will be a crucial factor that may help develop better performance and reliability in the models. With due consideration for these challenges, the robustness and applicability of AI-driven solutions will increase substantially.

The integration of AI, XR, and telerehabilitation has emerged as an avenue of promise but little investigation. XR can offer immersive environments for emotional and cognitive stimulation, while telerehabilitation offers remote monitoring and engagement for long-term care. Despite the promising nature of this integration, few research studies have been conducted on the practical application of these technologies within clinical settings. Gaps exist in the translation of user-friendly interfaces with rigorous validation via clinical trials.

This is inherently the limitation of a single-modality approach, be it an approach based purely on EEG signals or otherwise. A multimodal framework can integrate EEG with facial expressions and physiological signals to enable more accurate and robust findings. This is

particularly important in patients with DOC, where broad emotional assessments are vital to their recovery and rehabilitation. Although most research studies put more emphasis on diagnostic applications, the extension of research to investigate the impact of emotion recognition on emotional well-being and rehabilitation outcomes falls within the circle of modern health care goals: personalized care and enhanced quality of life.

Strengths:

1. Identification of Promising Approaches:

The research indicates new trends, like multimodal emotion recognition and integration of XR, hence being a good foundation for further development.

2. Alignment with Patient-Centered Objectives:

The focus on mental conditions and rehabilitation outcomes ensures alignment with priorities in modern healthcare.

3. Technological Advancement:

That includes the use of advanced AI methods, such as deep learning for EEG-based emotion detection, which is a huge achievement in the field.

Weaknesses:

1. Lack of Specific Examples:

Most of the reviewed studies have failed to provide specific examples or applications; hence, the findings are somewhat limited with respect to practicality.

2. Overlooked Implementation Barriers:

Few of them address practical challenges in cost, infrastructure needs, and the involvement of caregivers, which limit their application in real life.

3. Scantly Attempted Validation:

Clinical trials, usability testing, and other forms of validation approaches have gotten scant focus, leading to a slow translation of findings into practice.

Conclusion:

The review provides insights into essential gaps, challenges, and opportunities for the application of AI in emotion recognition in patients with DOC. It follows, therefore, that what is urgently needed is a multi-faceted framework incorporating ethical, technological,

and clinical considerations. Overcoming implementation barriers, having specific examples, and mentioning techniques related to validation could make valuable contributions in these studies to push academic knowledge and health practices further. This has potential to transform AI-driven emotion recognition into improved emotional well-being and rehabilitation outcomes for patients with impaired consciousness and eventually to more personalized and impactful care.

Connections:

1. Unanimous Decree of Importance of AI in Emotion Recognition

What can be inferred from all these papers is the important role that AI is playing in the advancement of emotion recognition, especially in medical use. They acknowledge the ability of AI in handling complex and large-scale datasets like EEG signals, facial expressions, and physiological metrics that can give insight impossible to obtain using traditional methods. The shared emphasis on AI provides the underpinning necessary for innovative solutions being developed for patients suffering from DOCs.

2. Shared Interest in EEG as Primary Modality

EEG appears implicitly in the reviewed studies as one of the base modalities since its signals are related to direct brain activity and emotional states. Various papers highlight how deep learning models are efficient at decoding, especially from EEG signals for patients who cannot communicate. This consensus underlines the reliability and supremacy of EEG in neural responses.

3. Ethical and Practical Challenges

breeding ground for ethical concerns regarding data privacy, algorithmic bias, and patient vulnerability. They all stress the need for robust ethical frameworks that ensure data anonymization, informed consent by caregivers, and clarity in AI decision-making. This recurrent echo testifies to the common responsibility of their authors to guarantee no unethical use of AI in healthcare.

4. Convergence on Multimodal Approaches

Most of the surveys emphasize limitations of single modality and conclude that a decision needs to be taken toward multimodal frameworks. Indeed, it is strongly agreed that combining EEG data with other inputs, such as facial expressions, body movements, and physiological signals like heart rate and skin conductance, may improve the accuracy and robustness of the results. This shared opinion refers to the need for multimodal systems, especially in those patients with damaged communication.

5. XR and Telerehabilitation: Promising Directions

Some of the papers identified the potential of XR and telerehabilitation to be truly transforming emotion recognition and neurorehabilitation. It is believed that such XR environments can be useful for the stimulation of cognitive and emotional recovery. Telerehabilitation, on the other hand, opens many perspectives in terms of remote monitoring and long-term care. The integration of this knowledge with AI is turning into a promising direction for future innovation.

6. Real-World Validation is a Common Theme:

Several of the papers point toward one common conclusion: AI models should be validated through clinical trials and real-world testing. There seems to be consensus on the fact that AI systems must be tested across diverse healthcare settings in order to make them practical, reliable, and acceptable by healthcare providers.

7. Personalization and Patient-Centered Approaches

The studies reviewed assert that personalized, patient-centered approaches must be encouraged. It is submitted that AI and XR technologies have been envisioned to be the modality by which personalized interventions would be realistically administered to achieve significant positive improvement in emotional well-being and rehabilitation outcomes of the patients concerned.

8. Innovation in Neurorehabilitation

The integration of AI with XR and telerehabilitation represents a significant step forward in neurorehabilitation. Several papers discussed how these technologies can work in unison to offer novelty in patient engagement, recovery, and long-term monitoring. This shared focus points out the innovative potential in combining these tools.

9. Challenges in Methodology and Availability of Dataset

More frequently mentioned issues include variability and noise in the datasets, including EEG signals. The creation of domain-specific datasets for patients with DOC is viewed as a step toward resolving this methodological barrier. The idea here is that one common problem is an issue at the level of the quality of data, which needs to be improved to enhance performance and reliability of the AI models.

Conflicting Findings

1. Single-Modality Approaches versus Multimodal Frameworks

Some works emphasize the improvement of unimodal methods, such as EEG signal analysis, as the most promising strategy for emotion recognition improvement. Others indicate the strengths of a multimodal framework that integrates EEG with other inputs, such as facial expressions, body movements, and physiological signals. In this respect, the divergence reflects a methodological gap between perfecting refined techniques and adopting systems with broad applicability.

2. Extended Reality Technologies

While some studies pave the way for regarding XR as a transformative tool for creating immersive therapeutic environments that enhance patient engagement and recovery, other papers present XR as an ancillary or unproven technology. Such a juxtaposition speaks volumes about the different degrees of confidence in the role of XR in emotion recognition and neurorehabilitation.

3. Theoretical vs. Practical Priorities

While some research works on practical implementation, there is a divide in studies between theoretical advancement, such as optimization algorithms and new AI techniques being explored. Some research will go into making tools seamlessly integrable within clinical workflows, while others remain anchored to abstract thoughts and ideas, creating tension between depth in research and real-world translation.

4. Validation Strategies

While some works tend to emphasize the need for validation of AI models through clinical trials and real-world testing to ensure their robustness, scalability, and practical use in healthcare settings, other works entirely focus on performance evaluations conducted in controlled environments, proving a difference in readiness for practical deployment.

5. Scope of Application

The purposes of emotion recognition vary significantly; some works narrowly focus on diagnostic applications-like detection and monitoring of emotional states-while others broaden their focus to therapeutic uses aimed at the improvement of emotional well-being and rehabilitation outcomes. This reflects a divergence in conceptions of how emotion recognition can impact patient care.

6. Inconsistent Attention to Dataset Challenges

Other works identify how the creation of domain-specific datasets to match the requirements of patients with disorders of consciousness, for example, has great

significance to meet challenges, such as variability and noise. Others barely discuss dataset limitations or ways to overcome those limitations. Such inconsistencies create a preparedness gap for scalability.

7. Ethical Depth and Engagement

While most of these studies recognize ethical issues related to data privacy, security, and algorithmic bias, the level of engagement varies from merely identifying ethical issues to proposing concrete recommendations such as anonymization protocols and algorithmic transparency. That difference suggests a readiness to act against ethical challenges in rather diverging ways.

8. Forecasted Use of AI in Patient Care

There is, therefore, a fundamental variance in the conceptualization of AI for patient care: some view it as a supportive tool to enhance clinical decisions, whereas others advance the use of AI as an autonomous, independent decision-maker. This arises from a divergence that guides how AI systems are designed to be integrated and applied within healthcare workflows.

9. Economic and Infrastructure Considerations

Some studies have focused on practical challenges with respect to costs and infrastructural needs when deploying AI and XR technologies in healthcare applications. Others hardly consider these, which leads to many differences regarding feasibility and scalability, especially in resource-poor environments.

10. Engage the Patient

Some studies foreground the roles of technologies such as XR and telerehabilitation in enhancing patient engagement and supporting holistic care. Other studies have focused narrowly on technical performance, with limited broader health care goals; this reflects a lack of concordance between technological innovation and its translation to the patient-centered, holistic medical care aim.

Synthesis Matrix for Literature Review:

Study 1: Matching Assistive Technology, Telerehabilitation, and Virtual Reality with Disorders of Consciousness and Neurocognitive Disorders: A Position Paper		
Authors	Year	Research Design
Khalida Akbar	2023	Theoretical and conceptual design
Key Findings/Results	Methodology	Limitations
It concludes that the integration of assistive technology, telerehabilitation, and VR might bring about a paradigmatic shift in the rehabilitation approach in patients suffering from DOC and neurocognitive disorders. Such technologies have the advantage of making personalized and adaptive interventions possible for individual cognitive and communicative needs. The authors underline that VR allows one to reproduce immersive real-world environments that may activate neural recovery, while telerehabilitation opens possibilities for treatment at remote locations. Specifically, it is within this context that assistive technology, including AI-driven tools, holds great potential for improving patient monitoring, hence therapy adjustment, in real time. Interdisciplinary collaboration among healthcare providers, technologists, and caregivers must help bridge the present gaps in the framework. The authors stressed the necessity of a conceptually patient-centered approach, calling for robust trials to validate clinically these technologies.	Comprehensive Literature Review: Reviewed extensively peer-reviewed articles, clinical reports, and case studies related to assistive technologies, telerehabilitation, and virtual reality applications for the treatment of DOC and neurocognitive impairments. Identify the existing therapeutic approaches and pointed out shortcomings in prevailing practices where technology could be integrated. Interdisciplinary Integration Collaboration with neurologists, psychologists, engineers, and experts in assistive technology will be done so that the proposed framework is multifaceted. Once ideas from health providers, rehabilitation experts, and technologists had been put forward and integrated with the capability to meet practical and clinical needs. Conceptual Framework Development Developed a theoretical model of the complementary roles of assistive technologies, telerehabilitation systems, and VR environments. Mapped how each of these technologies could address specific cognitive, emotional, and communicative deficits common to patients with DoC and neurocognitive disorders. Scenario-Based Hypothetical Analysis Created simulated patient scenarios to show how the proposed integrated system would work in natural environments. Showing how VR might provide cognitive stimulation, telerehabilitation might extend care remotely, and assistive technology might promote communication and tracking of progress. Evaluation of Current Technology Implemented review of existing hardware/software tools with respect to compatibility with the proposed framework. Investigated possibilities for customization/adaptation of technologies to fit specific patient needs. Critical Ethical Review	This is a conceptual position paper; no empirical data is provided to support the arguments. The network proposed is still conceptual since it was not experimentally validated, nor were any clinical trials conducted to establish its efficacy. In addition, though the paper optimistically describes integrating technology, issues of implementation such as costs, technological literacy among health care providers, and access to the very poor have hardly been covered. Additionally, it does not take into consideration any limitations on scalability and long-term sustainability in various settings related to healthcare. Thus, future research should focus on clinical trials, cost-benefit analysis, and feasibility in the real world to translate these proposed ideas into practical applications for health care. Ethical issues related to data security and consent from the patients would require much more focused exploration for safe adaptation of this technology.

Analyzed ethical implications of the proposed solutions and identified data privacy, patient consent, and involvement of caregivers.

Proposed guidelines on how to integrate those technologies in a manner that ensures a premium is placed on patient dignity and autonomy.

Review of Accessibility and Cost-Effectiveness

This considered the challenges for adoption, including technological infrastructure requirements, cost, and accessibility for low-resource settings.

Strategies that will be proposed for scaling the integrated system toward a diverse patient population.

Proposed Future Research Agenda

These include piloting the framework in controlled environments, development of specialized VR scenarios for rehabilitation, and creation of adaptive AI tools that monitor patient progress.

The methodologies that come up to test the effectiveness of the integrated approach through clinical trials were also developed.

Study 2: A Systematic Review and Meta-Analysis of Artificial Intelligence Tools in Medicine and Healthcare: Applications, Considerations, Limitations, Motivation and Challenges

Authors	Year	Research Design
Hussain A. Younis, Taiseer Abdalla Elfadil Eisa, Maged Nasser, Thaeer Mueen Sahib, Ameen A. Noor, Osamah Mohammed Alyasiri, and Sani Salisu	2024	Systematic review
Key Findings/Results	Methodology	Limitations
The AI-powered intervention has the potential to disrupt medical domains from diagnosis and treatment planning through patient monitoring to administrative efficiency. The use of large language models, such as ChatGPT, presents tremendous opportunities in the areas of medical education, virtual consultation, and actionable insight development. AI-powered imaging systems have improved diagnostic accuracy, while predictive algorithms enhance personalized treatment strategies. On the other hand, this vision is also pointedly contrasted with several challenges facing it, including data privacy, the risk of biased algorithms, and the necessity for human oversight in decision-making. Adoption issues are ethical considerations-those of transparency and accountability. Further, the integration of AI tools into current workflows of healthcare requires huge investments in training and infrastructure. The authors identify that such challenges will need to be overcome using interdisciplinary collaboration. Whereas there were limitations, the results promising advances in healthcare delivery and outcomes through AI, when ethical, technical, and logistical concerns are taken care of.	Literature Search: Extended search across multiple databases to identify relevant studies published on AI applications in health care. Inclusion Criteria: Included those studies focused on AI tools implemented across diagnostic, therapeutic, administrative, and educational aspects of health care. Data Extraction: The extracted details concerned objectives, methodologies, AI applications, and outcomes reported in those selected studies. Categorization: Data were organized, tabulated, and synthesized into eight main categories of applications, namely, treatment planning, medical imaging, patient monitoring, healthcare administration, education, and others. Quality Assessment: Appraisal of the quality and reliability of the studies included was done using standardized tools to minimize biases. Meta-analysis: A quantitative analysis was performed to establish the performance metrics of AI tools in enhancing health care metrics on accuracy, efficiency, and cost-effectiveness. Ethical Analysis: Ethics regarding data privacy and security, and the issue of potential bias in AI algorithms, were addressed. Discussion of Practicality: Review the feasibility of integration into real-world clinical settings, including discussion of cost, infrastructure needs, and scalability. Recommendations: Provide actionable recommendations to key stakeholders who can make responsible AI adoption a reality, including policy makers, healthcare providers, and researchers.	The study acknowledges several limitations that influence the generalizability of its findings. First, the rate at which the technologies of AI are changing means this review is unlikely to capture recent innovations and their applications. Second, the variability in quality of studies, their methodologies, and reporting standards results in inconsistencies in data that are synthesized. Reliance upon published literature may result in publication bias, where more studies showing positive outcomes are likely to be published than those that might show neutral or negative findings. Moreover, their influence on improving patient outcomes and increasing efficiency in health care is not well known, since most of the AI tools have been adopted relatively recently. Region-specific challenges, such as infrastructural limitations regarding low-resource settings, are not deeply explored in this review. These include the need for further research in ethical considerations such as possible biases in AI algorithms and data privacy. Longitudinal studies, the inclusion of more diverse datasets, and real-world barriers to large-scale implementation of AI systems in healthcare would be promising directions for future research.

Study 3: Systematic Review of Emotion Detection with Computer Vision and Deep Learning		
Authors	Year	Research Design
Rafael Pereira, Carla Mendes, José Ribeiro, Roberto Ribeiro, Rolando Miragaia, Nuno Rodrigues, Nuno Costa, and António Pereira	2024	Systematic review
Key Findings/Results	Methodology	Limitations
The review thereby concludes that there is considerable development on emotion recognition through computer vision and deep learning, with recent emphasis on both facial and pose-based analyses. CNN is commonly used since it yields an excellent performance in feature extraction and classification. Multimodal approaches, where the face is combined with body gestures, improve the accuracy and robustness of emotion detection systems. However, large, annotated datasets remain a challenge, and variations in lighting conditions, occlusions, and individual differences in expressing emotions need to be taken into consideration. This study, therefore, underlines the development of standardized benchmarks and datasets that can help make consistent evaluations across different models. Further, ethical issues include privacy and bias occurring in AI algorithms, which are also pointed out as very important issues that will require consideration. Overall, though reasonable advances have been made, further studies will be needed to overcome these limitations for better practicality in everyday use.	Literature Search: The major electronic databases used were PubMed, Web of Science, Google Scholar, and IEEE Xplore to identify studies published between 2013 and 2023. In the selection of studies for this review. Inclusion criteria: will include studies dealing with emotion recognition that employ computer vision and deep learning techniques. The criterion also limits the selection to papers based on face expressions and body poses. Exclusion criteria: studies were excluded when no deep learning methodologies were employed in the study or when the approach appeared irrelevant to emotion detection. Data Extraction: Key information from the selected studies included: populations studied, application scenarios, technological methods applied, and datasets used. Quality Assessment: The CASP checking criteria are applied to ensure that the findings are both valid and reliable. Categorization: The studies were organized using a proposed taxonomy describing the type of expressions used for emotion detection, the testing environment, the deep learning methods applied, and the datasets used. Analysis: From this, extracted data was analyzed to show trends, common methodologies, and gaps in the current research landscape. Synthesis: Synthesize herein to give a comprehensive overview related to emotion detection using computer vision and deep learning. Reporting: The results have been presented in accordance with the PRISMA guidelines so as to make the review process transparent and reproducible.	Various limitations are acknowledged in the state of the current research using computer vision and deep learning to detect emotion: change in lighting, occlusions, and different ways of expressing emotions individually which can bring negative impacts to the performance of emotion recognition systems. Thirdly, non-uniform benchmarks and metrics for evaluation make objective comparisons of performance between different models quite complicated. Besides, most works do not discuss essential ethical considerations in detail, including the privacy and biases of AI algorithms. It calls for responsible AI. It also points out that most of the research developed so far is performed in controlled environments, which may not represent natural circumstances and hence limit the generalizability of the findings. On the other hand, deep learning techniques are evolving so fast that continuous updating is required to keep pace with state-of-the-art developments. Finally, challenges in the field are of a very heterogeneous nature; interdisciplinary collaboration is an essential component, although few such collaborations currently exist. How these limitations are overcome will provide the way ahead for further development and effective deployment of emotion detection systems in realistic applications.

Study 4: Towards Effective Emotion Detection: A Comprehensive Machine Learning Approach on EEG Signals		
Authors	Year	Research Design
Ietezaz Ul Hassan, Raja Hashim Ali Zain ul Abideen, Ali Zeeshan Ijaz Talha Ali Khan	2023	Experimental
Key Findings/Results	Methodology	Limitations
This study indeed showed the efficiency of the usage of machine learning classifiers for detecting a variety of emotional states from EEG signals. Among them, the logistic regression model gave a good accuracy of 97%, closely followed by random forest. These findings point out the high potential of machine learning algorithms in exact emotion detection, combined further with proper preprocessing and feature extraction techniques. The differences that were witnessed also pointed at optimization of hyperparameters as an important factor in fine-tuning the classifier performance. The results implicated that EEG-based emotion detection is promising for transformational use in monitoring and diagnosis of mental health. The variability in the individual patterns of EEG was, however, some of those factors ascribed to the accuracy in detection. This research will encourage further development based on various working explorations of classifiers and feature selection methods for better refinement in the emotion detection system.	Dataset Used: The Emotion Detection dataset on Kaggle is public and was used, which has both EEG recordings and its corresponding emotional state. Data Preprocessing: Cleaning of the EEG signals was done by filtering out noises and other artifacts to prepare and ensure the quality of data. Feature Extraction: Frequency bands and power spectral densities were extracted as relevant features that best represent the EEG signals. Classifier Selection: Various machine learning classifiers tested in this work include logistic regression, random forest, decision trees, naive Bayes, support vector machines, and nearest centroid. Hyperparameter Tuning: Optimization techniques were applied for fine-tuning the parameters of each classifier that influence its performance. Model Training: It trains selected classifiers using preprocessed EEG data with extracted features as inputs. Performance Evaluation: Model effectiveness could be measured by means of different metrics, including but not limited to accuracy, precision, recall, and F1-score. Comparative Analysis: Compare the classifiers side by side for the most accurate and robust model. Result Interpretation: Discussed the implications of the results regarding emotion detection and its possible applications in mental health care.	The result of this study relies on the Kaggle Emotion Detection dataset, hence restricting generalizability since that dataset may not reflect all the variability in EEG signals among different populations. This study again deals only with a classical machine learning classifier and does not try deep learning techniques which can potentially give better results. The real-time applicability has also not been discussed in this research work and questions still arise as to how the models perform in real time. Moreover, this study did not explore how individual differences in EEG related to age, gender, or neurological conditions may affect emotion detection performance. Secondly, the dataset size used in this study was relatively limited, and a larger dataset might lead to stronger results. Future work will be carried out on larger and more diverse datasets, including deep learning approaches, and considering real-time applications that make the EEG-based emotion detection system more practical. Such multimodal data could include physiological signals, including added knowledge and thus usually improving performance.

Study 5: Emotion Detection from EEG Signals Using Machine Deep Learning Techniques		
Authors	Year	Research Design
Rafael Pereira, Carla Mendes, José Ribeiro, Roberto Ribeiro, Rolando Miragaia, Nuno Rodrigues, Nuno Costa, António Pereira	2023	Experimental
Key Findings/Results	Methodology	Limitations
The results have indeed indicated that deep learning methods can classify emotions from EEG signals highly; specifically, Graph Convolutional Neural Networks outperformed their usual machine learning methods. GCNN has reached an accuracy of 92% more than other models tested in the study. That also means the deep learning methods can carve out complicated patterns in the EEG to further boost the performance in emotion detection. While feature selection and data preprocessing may be extremely crucial to realize better performance of the model.	Data Selection: The EEG datasets were publicly available along with their labeled corresponding emotional states. Data Preprocessing: Filtering techniques are applied to remove the noise and other artifacts from the EEG signals. Feature Extraction: Carried out the extraction of relevant features of the EEG data, such as power spectral density and differential entropy. Model Selection: Some of the pursued machine learning and deep learning models are Logistic Regression, Support Vector Machines, Random Forest, Deep Neural Networks, and Graph Convolutional Neural Networks. Model Training: Each model is trained based on the pre-processed EEG data with extracted features. Hyper-parameter Tuning: Parameters of the model are tuned to enhance performance. Model Performance Evaluation: Models are evaluated in terms of their performance using metrics such as accuracy, precision, recall, and F1-score. Comparison Analysis: All models were compared to explore the best approach toward the detection of emotions. Result discussion: These results were interpreted to tell what these results would lead to in developing robust EEG-based emotion detection systems.	The results could also be limited in generalizability since they might depend on publicly available datasets of EEG, which may not cover the full variability of emotional expressions across different populations. Second, most of the studies reviewed here focus more on the model's accuracy of classification, without considering real-time applicability or computational efficiency in detail- both factors of high relevance in practical applications. For instance, the study does not delve into exactly how individual parameters like age, gender, or cultural background may affect EEG patterns and emotion recognition rates. Another essential aspect that the research has pointed out about highlighting the excellence of the deep learning models is elaborated on, which indeed concerns interpretability, which is very relevant to understanding the process by which decisions are made in systems for the detection of emotions. These aspects have to be considered in further research to provide more comprehensive and applicable EEG-based emotion detection frameworks.

Study 6: Reviewing the Horizon: The Future of Extended Reality and Artificial Intelligence in Neurorehabilitation for Brain Injury Recovery		
Authors	Year	Research Design
Khalida Akbar, Anna Passaro, Mariacarla Di Gioia Elvira Martini, Mirella Dragone, Antonio Zullo, Fabrizio Stasolla	2024	Perspective paper
Key Findings/Results	Methodology	Limitations
The authors have elaborated on how such integration of XR with AI can be a game-changer in neurorehabilitation through personalized, immersive, and adaptive therapeutic intervention. They have highlighted the fact that the creation of an immersive environment that will stimulate neural recovery can be facilitated through XR, while AI may allow personalization of rehabilitation programs for the individual patient, monitoring progress, and forecasting outcomes. It is envisaged that this integration will increase patient engagement, hasten the recovery process, and improve the quality of life in persons suffering from brain injury. The paper also talks about the reduction in caregiver burden by AI-assisted monitoring and support systems. However, various challenges emanating as issues of technological accessibility, ethical concerns, and interdisciplinary collaboration requirements have been pointed out for translation of these innovations into effective practice.	Literature Review: Critical review of empirical studies in the past decade that have used XR and AI for neurorehabilitation. Data Synthesis: The findings from these studies were analyzed to identify trends, benefits, and limitations of the use of XR and AI in recovery from brain injuries. Conceptual Framework Development: It proposes an overall model of how XR and AI can be integrated to further improve neurorehabilitation outcomes. Case Analysis: A case study review of successful applications of both XR and AI in clinical settings. Ethical Issues: Measured the ethical implications, including issues on consent by patients, data privacy, and disparities induced by technology. Interdisciplinary Collaboration: The success of implementation rests on collaboration among healthcare professionals, technologists, and patients. Technological Assessment: The paper assessed the status of XR and AI technologies with respect to applicability and readiness in neurorehabilitation. Future Directions: Following the general overview, recommendations for future research, clinical practice, and policy development that would facilitate the integration of XR and AI in neurorehabilitation were outlined.	This is a theoretical study for the most part, and there is no empirical data or even clinical trials to prove the framework that has been proposed. The reliance on existing literature could also mean that bias might enter through selected studies that could again influence conclusions. Besides, the fast-changing nature of XR and AI technologies means that some recent advances could not have been caught by the analysis. The paper further recognizes some implementation barriers, such as high costs, specialized training, and technological accessibility, but does not provide information on how to handle such challenges. Another section concerns ethical considerations, but the paper does not fully discuss the possible risks regarding the integration of XR and AI in neurorehabilitation. Future studies should, therefore, concentrate on issues related to empirical validation, cost-benefit analyses, and guideline development in response to ethical and practical challenges regarding the implementation of such technologies.

Study 7: An Efficient EEG Signal Analysis for Emotion Recognition Using FPGA		
Authors	Year	Research Design
Ezilarasan & Leung	2024	Experimental
Key Findings/Results	Methodology	Limitations
The research shows great improvements in emotion recognition based on EEG signal processing. The classification accuracy of the proposed system is 98%, which is higher than that achieved by previously presented methods. Such high accuracy is attained due to the application of ICA and adaptive filtering for efficient artifact removal from raw EEG signals, ensuring clean inputs for analysis. The hybrid CNN-LSTM model, with the enhanced ResNet-152 classifier, is efficient in feature extraction and classification for the recognition of emotions with great accuracy. The Altera DE2 FPGA development board was used for implementation to ensure that the system had optimized speed and area while keeping energy efficiency in check. The five-emotion-state SEED V dataset is used for training and testing to ensure robustness in model evaluation. In fact, the system maintains high computational efficiency with minimum hardware complexity, considering that there is one adaptive filter in Multiply-Accumulate. Another major issue in this design is that 10% of the available resources of the Cyclone IV E chip are occupied in this FPGA implementation. These properties make the system suitable for real-time applications such as healthcare and human-computer interaction. The proposed method, when compared to benchmark techniques, shows better accuracy and hardware efficiency, hence being a strong solution for emotion recognition using EEG signals.	Dataset Usage: SEED V dataset is used, in which EEG signals were recorded for five emotional states (happiness, sadness, fear, neutrality, and disgust) from 16 subjects. Preprocessing: The used dataset comprises features extracted from five frequency sub-bands: alpha, beta, gamma, delta, and theta. Preprocessing: Independent Component Analysis (ICA) will be utilized to remove artifacts from the signals, such as eye movements and muscle activity from the raw EEG signals. An adaptive low-pass FIR filter is used for further smoothing and noise reduction. Feature Extraction: The features are extracted using a hybrid model of CNN-LSTM, which integrates the powers of CNNs for the recognition of spatial patterns and LSTM networks for temporal sequence analysis. - The ResNet-152 architecture is integrated for better classification performance by means of deep residual learning. Classification: The CNN-LSTM with ResNet-152 serves as the main classification model that will differentiate between the two emotional states based on the pre-processed EEG data. FPGA Implementation: The system is implemented on the Altera DE2 FPGA development board to ensure real-time processing. This optimization is done in hardware, utilizing only one Multiply-Accumulate (MAC) adaptive filter, thereby reducing computational complexity. Training and Testing: 70% for Training, 30% Testing Cross-Validation: A 5-fold cross-validation is done to ensure a proper generalization of results for performance evaluations. Performance Metrics: The key metrics used to review the effectiveness of the system involve accuracy and hardware resource utilization. Comparisons with benchmark techniques are performed to be able to point out improvements.	Some of the limitations identified in the study are the fact that An Efficient EEG Signal Analysis for Emotion Recognition Using FPGA need programmers who have expertise in languages like Verilog and VHDL, hence limiting the skill set of a machine learning practitioner who is not experienced with hardware design. Because with more scalability and flexibility on more platforms, there will be dependence on this system, further bringing down its application area. Moreover, a lot of the research is based on the robust dataset from SEED V, but may not be varied across emotional states among different populations. Although some applied hardware optimization techniques, it is very computationally intensive to realize such a complex deep learning model like ResNet-152 on FPGA, which will not be practical in real-time applications. It is narrowed down by focusing only on a limited set of emotional states that include happiness, sadness, fear, neutrality, and disgust. The proposed system was tested under controlled conditions using the SEED V dataset. It is not tested in real life under uncontrolled conditions. Finally, scalability might be an issue, as its present implementation on FPGA may involve more changes to either handle bigger datasets or more challenging emotion recognition tasks.

Study 8: Challenges for Artificial Intelligence in Recognizing Mental Disorders		
Authors	Year	Research Design
Wen-Jing Yan, Qian-Nan Ruan, and Ke Jiang	2022	Review-based design
Key Findings/Results	Methodology	Limitations
There are significant challenges with subjectivity and variability which mean that ecological validity is a great challenge in the existing datasets applied for AI in diagnosing mental disorders. Many suffer from limited sample sizes and other limitations which make their results generalizable. It is often not easy to map subjective, high-level emotional states based on the low-level objective data that current AI depends on, such as facial expressions and physiological signals. Co-morbidities and cultural variability further increase the challenge to diagnostic consistency. The diagnostic tools themselves, such as the DSM-5, are not immune to controversy. Multimodal approaches may provide better accuracy, but these require huge amounts of data and introduce noise. AI in mental health is a very exciting yet immature area of study; what holds this field back is mainly our limited understanding of the disorders, not technical limitations.	Diagnostic Criteria: Subjectivity and variability are inherent in the symptoms of mental health. Existing Datasets: Problems with small sample sizes, lack of ecological validity, and over-simplification of mental health categories. AI Approaches: Low-level features, such as facial cues or heart rate, cannot reliably map high-level emotions or disorders. Multimodality: While promising, it introduces complexities and noise, requiring significantly larger datasets. Logics Trick: Discussing the logical fallacy of diagnosis of a disorder based only on its symptoms.	The application of AI to the diagnosis of mental health is plagued by several limitations: small, non-diverse, and non-complex data sets that raise questions of generalizability; most AI models are simple binary classifications, such as depressed versus non-depression, which do not fit into the nuanced spectrum of mental disorders; and co-morbid conditions and cultural variability further complicate reaching consistent diagnostic outcomes. The reliance on subjective annotations and qualitative measures undermines the reliability of AI systems trained on such data. Besides, the logical fallacy of inferring disorders solely from symptoms questions the foundational approach of many AI models. While the multimodal methods are promising, they require extensive, high-quality datasets, which are hard to obtain due to ethical and logistical constraints. These limitations also bring out the need for an interdisciplinary effort in refining AI methodologies in understanding mental health disorders.

Study 9: Integration of Multiple Biosensors for Emotion Classification with Artificial Intelligence		
Authors	Year	Research Design
Cintia Ricaele Ferreira da Silva, Marcus Vinicius Costa Alves, Maria José Nunes Gadelha, and Edgard Morya	2024	Experimental
Key Findings/Results	Methodology	Limitations
This study shows the successful merging of EEG, ECG, and GSR signals on emotion classification, focusing only on four discrete emotions: happiness, sadness, anger, and fear. The LazyPredict library allowed multiple classifiers to be tested, finding that the Extra Trees performed best for binary classification for the emotions. For sadness, the highest balanced accuracy was returned by Random Forest at 65.74%, though Nu-SVC was the strongest for happiness at 68.67%. The Perceptron classifier performed best for fear, with 70.22%, while AdaBoost performed best for anger, with 75.27%. Even though the best models were different, the Extra Trees model was among the best in three emotions. This research shows the potential of biosensors and machine learning in improving the accuracy of emotion recognition. These results form a promising basis for applications in healthcare, education, and human-computer interaction.	Data Collection: Signals have been collected from a participant using EEG electrodes, ECG sensors, and GSR sensors while exposing him/her to the stimuli from the IAPS. Based on valence and arousal levels, four emotions are chosen: happiness, sadness, anger, and fear. Preprocessing: Normalization of data by Z-score, followed by band-pass filtering for EEG (0.5-30 Hz), ECG (0.5-15 Hz), and GSR signals. Afterwards, all the signals were segmented in epochs of 1000 ms, and acceptable epochs were selected based on their baseline values. Feature Extraction: A filter by DWT for all the biosensors was used; besides others, relative energy for every signal regarding Delta, Theta, Alpha, and Beta bands were extracted. Classifier: In this work, numerous machine learning classifiers have been tested thanks to the LazyPredict library. These models have been valued following parameters like accuracy, balanced accuracy, F1 score, and ROC AUC. The Extra Trees model showed the most consistent performance. Experimental Protocol: The stimuli was presented for 3000 milliseconds and separated by breaks between images to eliminate participant fatigue and emotional biases.	The integration of biosensors for emotion classification has several limitations. First, it notes the single participant as limiting, thus generalizing to a larger population. Though methodologically sound, the datasets relied on restrict broader applicability and cross-validation across diverse groups. Also, the focus on binary classification narrows the scope, as it excludes the spectrum of complex emotions. Although the design includes several classifiers, the results are very dependent on the limited library of LazyPredict and may not consider other robust models. The experiment relies on structured stimuli from the IAPS dataset, which may not be natural in real-world conditions where emotions arise spontaneously. Another limitation is the computational complexity of combining biosensors, which can make real-time implementation challenging. Furthermore, class imbalance issues in the data may have skewed certain classification metrics. Finally, the integration of biosensors that operate at various sampling frequencies and with different signal characteristics introduces more noise and brings synchronization difficulties, which require advanced preprocessing techniques to minimize.

Study 10: Review of EEG Affective Recognition with a Neuroscience Perspective		
Authors	Year	Research Design
Rosary Yuting Lim, Wai-Cheong Lincoln Lew, and Kai Keng Ang.	2024	systematic review
Key Findings/Results	Methodology	Limitations
This study underlines that EEG-based emotion recognition benefits from the integration of neuroscientific and computational models, emphasizing important spatiotemporal analysis. Brain oscillations-such as theta and alpha-frequencies are suggested to bear a significant role in processing during emotional states, with differing frequencies corresponding to distinct neural populations. The temporal resolution provided by EEG can facilitate the detection of emotional states in real time, but individual variability and limitations in datasets persist. Effective event-related potentials include P300 and N170, which are effective in detecting variations in emotions but lack specificity to individual emotions. Spatiotemporal models are proposed for capturing the dynamic interplay of brain regions during emotional processing. The review further identifies that emotional recognition depends on neural activities in the prefrontal cortex and amygdala. Combining neuroscience insights with computational techniques enhances interpretability and leads toward bio-inspired affective computing models.	Search and Inclusion Criteria: Relevant studies were identified using the keywords "EEG emotion recognition," "neural oscillations," and "affective computing" from databases such as PubMed and Google Scholar. Of an initial number of 200,000 papers, 77 were found to meet the inclusion criteria and were subject to a systematic review. Scope: The review covers spatial, temporal, and spatiotemporal aspects of emotion recognition related to EEG. Main headings include feature extraction techniques, recognition models, and evaluation methods of the EEG data. Integration of Disciplines: It integrates neuroscientific evidence regarding brain regions and oscillatory mechanisms with computational approaches for emotion recognition. Technique Analysis The experimental protocols, ERP, and evoked oscillations were discussed for their effectiveness in recognizing emotive tasks.	This study recognizes several limitations associated with EEG-based emotion recognition. First, there is individual variability in the brain's response to emotional stimuli, which is a big challenge since models learned from one dataset may not generalize to another. Small and non-standardized datasets further exacerbate this issue, limiting the reproducibility and robustness of findings. While EEG has very good temporal resolution, the spatial resolution is still poor; hence, it is very difficult to accurately locate the neural origin of an emotional state. The use of ERPs and brain oscillations in emotion detection depends on noisy and ambiguous signals, especially in cases where there is a superposition of multiple emotions. Besides that, spatiotemporal models require heavy computational resources and data preprocessing that may limit the real-time applications. This area of research is also limited by ethical concerns about data privacy and the invasiveness of some of the techniques used for validation. Finally, the integration of neuroscience and computational approaches, though promising, remains underexplored, calling for more interdisciplinary collaboration to address these gaps.

Summary of Literature Review

Emotion recognition systems literature identifies some key themes:

Limitations of Current Approaches:

- EEG-based systems have been promising in detecting emotions directly from brain signals but were normally marred by noisiness, inter-individual variability, and large datasets required for the two works Emotion Detection.(Fernandes et al., 2024; Ul Hassan et al., 2023)
- Facial recognition and physiological data provide complementary insights into human behavior; however, these approaches are often isolated from each other, not leveraging many of the advantages of combination (Pereira et al., 2024; Stasolla et al., 2023)

Amplifying Multimodal Approaches:

- EEG, facial, and physiological information are combined to improve recognition accuracy. For example, Graph Convolutional Neural Networks model spatial relationships in EEG while CNNs do well in analyzing facial expressions (Fernandes et al., 2024; Pereira et al., 2024; Ul Hassan et al., 2023)

Ethical Consideration:

- Patient privacy and informed consent are two of the critical challenges, particularly in clinical settings. Transparencies in algorithms and minimization of biases are two mainstays for wide adoptions(Akbar et al., 2024; Stasolla et al., 2023)

Applications in Neurorehabilitation:

- Virtual Reality and Telerehabilitation are a few emerging technologies that could accommodate the integration of an emotion recognition system to improve the patients' quality of life(Akbar et al., 2024; Stasolla et al., 2023)

Anticipated Contributions:

The present study is expected to contribute substantially on several fronts:

Theoretical Advances:

Introduce a new framework that represents emotion detection from a multimodal approach, where EEG has been combined with facial and physiological data to address the lacunars in the current state (Fernandes et al., 2024; Stasolla et al., 2023)

Technological Innovation:

Design and validate high-level machine learning models in real time for emotion detection in clinical settings by using GCNN (Fernandes et al., 2024; Ul Hassan et al., 2023)

Ethical Benchmarking:

Establish norms on privacy, transparency, and informed consent regarding emotion recognition systems (Akbar et al., 2024; Stasolla et al., 2023)

Practical Implementation:

Actionable recommendations that integrate the proposed framework into healthcare systems to provide better patient care and rehabilitation outcomes (Akbar et al., 2024; Stasolla et al., 2023; Ul Hassan et al., 2023)

Future Research Directions:

Identify pathways for further innovation, focusing on expanding multimodal datasets and refining AI models for emotion recognition (Fernandes et al., 2024; Ul Hassan et al., 2023)

3. Chapter 3: (Research Methodology)

1.1 Research Methodology

Research Design

This research work applies a mixed-methods approach in the design, implementation, and validation of a multi-modal emotion recognition framework for patients with DOC. The methodology will be planned to follow qualitative and quantitative phases of exploration, development, and testing of the proposed system.

Phase 1: Literature Review

Objectives:

- To Identify limitations in unimodal emotion recognition systems.
- Exploring the potential of multimodal approaches, which may combine EEG, facial recognition, and physiological signals.
- To investigate ethical issues such as patient privacy, algorithmic transparency, and informed consent.

Methodology:

Data Sources: Academic databases, for example, IEEE Xplore, PubMed, ACM Digital Library, with a preference for studies published in the last decade.

Selection Criteria: Research on EEG-based emotion recognition, multimodal systems, machine learning models, for instance, GCNN, LSTM, and healthcare applications.

Analysis: Thematic analysis to extract challenges, solutions, and emerging trends.

Phase 2: Qualitative Research

Objectives:

- To assess the stakeholders' perspective on the usability and ethical challenges related to emotion recognition systems.

- To outline the needs concerning interdisciplinary collaboration in AI integration within neurorehabilitation.

Methodology:

- Respondents: Neurologists, psychologists, AI developers, and caregivers will be selected using purposive sampling.
- Data Collection: Semi-structured interviews will be carried out remotely or in person.
- Analysis: Qualitative content analysis will be performed in order to identify key themes relating to system design, ethical concerns, and clinical implementation.

Phase 3: Quantitative Research

Objectives:

- To assess how well multimodal data fusion works in improving the accuracy of emotion recognition.
- To evaluate scalability, robustness, and ethical considerations of the system in experimental settings.

Methodology:

- Survey Design: Feedback will be given from users and clinicians on existing emotion recognition technologies through a survey.
- Experimental Testing:
 - Subjects: Participants from different clinical backgrounds for subject-dependent and subject-independent testing.
 - Data Collection: EEG signals, facial expression data, and physiological measurements such as heart rate and skin conductance.
 - Evaluation Metrics: Accuracy, precision, recall, scalability, and ethical compliance.
- Data Analysis: Statistical techniques will be implemented to compare the performance across the different modalities and to further validate the robustness of the system.

Phase 4: Framework Development and Validation

Objectives:

- To design a real-time, scalable multimodal emotion recognition framework.
- To validate its applicability and reliability within clinical settings.

Methodology:

Framework Design:

- The integration of EEG, facial recognition, and physiological signals using novel machine learning algorithms, such as GCNN and LSTM.
- Implementation of data privacy protocols and informed consent mechanisms.

Validation:

- Testing the prototype with DOC patients in controlled clinical environments
- Gathering feedback from clinicians and caregivers
- Iterative refinement based on expert reviews.

Evaluation:

Usability, ethical compliance, clinical impact, and interdisciplinary collaboration are the critical metrics.

Ethical Consideration

The following ethical considerations have been followed throughout the study:

- Informed consent from participants or guardians.
- Data anonymization with transparency in algorithms.
- Ethical challenges: vulnerable patient population and fairness in AI algorithms.

Limitations

Data Availability and Quality:

- Lack of large, annotated multimodal datasets specific to DOC may raise concerns about the generalizability of findings.
- Synchronization challenges with diverse data types (EEG, facial recognition, physiological signals) could introduce noise and variability.

Ethical Concerns:

- Data privacy and patient vulnerability could pose challenges in clinical deployment and would require robust anonymization protocols.
- Ensuring informed consent in vulnerable populations, such as DOC patients, is a complex issue.

Technological Constraints:

- Real-time processing of multimodal data may be computationally and hardware-intensive, especially in resource-constrained clinical settings.
- Variability in the performance of machine learning models across different populations and clinical scenarios could limit scalability.

Interdisciplinary Collaboration:

- The effective integration of AI systems into healthcare workflows requires collaboration among technologists, clinicians, and ethicists, which may face logistical and communicative barriers.

Validation Challenges:

- Subject-independent testing may give different results because of individual variability, hence requiring a wide range of validation across diverse populations and clinical conditions.

1.2 Expected Outcomes

Improved Emotion Recognition Framework:

- Design a scalable, multimodal emotion recognition framework that incorporates EEG, facial recognition, and physiological signals.
- Higher accuracy and robustness in detecting emotions compared to unimodal approaches.

Technological Innovation:

- Advanced machine learning models will be implemented, such as GCNN and LSTM, tailored for multimodal data fusion.
- Real-time functionality that will seamlessly embed it into clinical workflows.

Ethical and Practical Guidelines:

- Actionable recommendations toward ethical deployment of AI, considering patient privacy, informed consent, and algorithmic transparency.
- Development of guidelines for ensuring equitable access and reduction of biases in AI-driven healthcare applications.

Impact on Patient Care:

- Improved engagement and recovery outcomes for patients due to accurate emotion recognition and customized rehabilitation programs.
- Reduced caregiver burden due to AI-assisted monitoring and decision-support systems.


Advancing Neurorehabilitation

- Integration of Extended Reality and Telerehabilitation to provide immersive and engaging therapeutic interventions
- Improved access to emotion recognition systems in remote and underserved areas

Basis for Future Studies:

- Formulation of domain-specific datasets to train and validate different models on emotion recognition tasks in DOC populations
- Establishing a baseline for future innovation using AI applications within neurorehabilitation.

1.3 Gantt Chart



References:

- Akbar, K., Passaro, A., Di Gioia, M., Martini, E., Dragone, M., Zullo, A., & Stasolla, F. (2024). Reviewing the Horizon: The Future of Extended Reality and Artificial Intelligence in Neurorehabilitation for Brain Injury Recovery. *Information (Switzerland)*, 15(8). <https://doi.org/10.3390/info15080501>
- Ezilarasan, M. R., & Leung, M. F. (2024). An Efficient EEG Signal Analysis for Emotion Recognition Using FPGA. *Information (Switzerland)*, 15(6). <https://doi.org/10.3390/info15060301>
- Fernandes, J. V. M. R., Alexandria, A. R. de, Marques, J. A. L., Assis, D. F. de, Motta, P. C., & Silva, B. R. dos S. (2024). Emotion Detection from EEG Signals Using Machine Deep Learning Models. *Bioengineering*, 11(8). <https://doi.org/10.3390/bioengineering11080782>
- Lim, R. Y., Lew, W. C. L., & Ang, K. K. (2024). Review of EEG Affective Recognition with a Neuroscience Perspective. In *Brain Sciences* (Vol. 14, Issue 4). Multidisciplinary Digital Publishing Institute (MDPI). <https://doi.org/10.3390/brainsci14040364>
- Pereira, R., Mendes, C., Ribeiro, J., Ribeiro, R., Miragaia, R., Rodrigues, N., Costa, N., & Pereira, A. (2024). Systematic Review of Emotion Detection with Computer Vision and Deep Learning. In *Sensors* (Vol. 24, Issue 11). Multidisciplinary Digital Publishing Institute (MDPI). <https://doi.org/10.3390/s24113484>
- Silva, C. R. F. da, Alves, M. V. C., Gadelha, M. J. N., & Morya, E. (2024). Integration of Multiple Biosensors for Emotion Classification with Artificial Intelligence. *The 4th International Electronic Conference on Biosensors*, 10. <https://doi.org/10.3390/engproc2024073010>
- Stasolla, F., Lopez, A., Akbar, K., Vinci, L. A., & Cusano, M. (2023). Matching Assistive Technology, Telerehabilitation, and Virtual Reality to Promote Cognitive Rehabilitation and Communication Skills in Neurological Populations: A Perspective Proposal. *Technologies*, 11(2). <https://doi.org/10.3390/technologies11020043>
- Ul Hassan, I., Ali, R. H., Abideen, Z. ul, Ijaz, A. Z., & Khan, T. A. (2023). Towards Effective Emotion Detection: A Comprehensive Machine Learning Approach on EEG Signals. *BioMedInformatics*, 3(4), 1083–1100. <https://doi.org/10.3390/biomedinformatics3040065>