

Student Name: Ghada Alenazi

Student ID: 261002011

Course Title: Research Methodology in Computer Science (AI800)

Lecturer: Dr. Mohammed Anbar

Assignment Report: Machine Learning and Deep Learning Approaches for Recommendation Systems

Table of Contents

Introduction	3
Summary research paper's	3
Paper 1: Wide & Deep Learning (2016)	3
Paper 2: Neural Collaborative Filtering (2017)	3
Paper 3: Hybrid CTR Model (2019)	4
Paper 4: LightGCN (2020).....	4
Paper 5: Context-Aware Recommendation (2020)	4
Paper 6: Self-Attention Sequential Model (2021).....	4
Critical Analysis	5
Synthesis of Information	5
Synthesis Matrix	6
Datasets and Evaluation Metrics	7
References.....	8

Introduction

This report provides a comprehensive review and critical analysis of six key research papers in recommendation systems. It compares methodologies, evaluates strengths and limitations, and synthesizes insights across studies to reflect the evolution of modern recommendation techniques.

Summary research paper's

Paper 1: Wide & Deep Learning (2016)

This paper introduces a model that combines a linear component (wide) with a deep neural network (deep). The wide part focuses on memorizing common feature interactions, while the deep part learns new patterns through embeddings. The main idea is that combining memorization and generalization leads to better performance than using either approach alone. The model was successfully applied in large-scale systems like Google Play. However, as the deep component becomes more complex, the model may become less efficient for real-time applications.

Paper 2: Neural Collaborative Filtering (2017)

Neural Collaborative Filtering replaces traditional matrix factorization with neural networks to model user–item interactions. By using a Multi-Layer Perceptron (MLP), the model captures complex nonlinear relationships. It also combines Generalized Matrix Factorization (GMF) with deep learning to represent both linear and nonlinear patterns. While this approach improves recommendation accuracy, it increases computational complexity, which can limit its use in latency-sensitive systems.

Paper 3: Hybrid CTR Model (2019)

This paper focuses on click-through rate prediction and introduces a hybrid deep learning model that automatically learns feature interactions. By combining factorization techniques with deep neural networks, the model captures complex relationships without requiring extensive manual feature engineering. Although it achieves strong performance on large datasets, it requires high computational resources, making it less suitable for lightweight or real-time environments.

Paper 4: LightGCN (2020)

LightGCN simplifies graph neural networks by removing feature transformations and nonlinear activation functions, keeping only neighborhood aggregation. This design reduces computational cost while maintaining strong performance. However, the model mainly focuses on user-item relationships and does not explicitly consider contextual information or temporal changes in user behavior.

Paper 5: Context-Aware Recommendation (2020)

This study highlights the importance of incorporating contextual information such as time, location, and device type into recommendation systems. By embedding these factors alongside user and item data, the model can generate more personalized and situation-aware recommendations. Despite its advantages, this approach is often not integrated with efficient graph-based models.

Paper 6: Self-Attention Sequential Model (2021)

This paper uses self-attention mechanisms to model user behavior over time. The model identifies the most relevant past interactions and assigns them higher importance, allowing it to capture both short-term and long-term preferences. While effective in dynamic environments, this approach adds computational overhead when combined with other complex models.

Critical Analysis

The reviewed studies show a clear shift toward more advanced models that better capture complex user behavior. While deep and hybrid approaches improve accuracy, they also introduce higher computational costs. LightGCN challenges the assumption that more complex models are always better by demonstrating that simpler architectures can achieve strong performance. Overall, a key challenge across these studies is balancing recommendation accuracy with computational efficiency, especially in real-time and resource-constrained environments.

Synthesis of Information

All studies emphasize the importance of embeddings in handling sparse data. In addition, hybrid models consistently outperform single-method approaches by capturing both simple and complex interactions. However, no single model is universally optimal. The effectiveness of a recommendation system depends on factors such as application context, scalability requirements, and available computational resources. These observations highlight the need for models that combine efficiency, contextual awareness, and the ability to capture evolving user preferences.

Synthesis Matrix

Study	Year	Method	Key Insight
Wide & Deep	2016	Linear + DNN	Memorization + Generalization
NCF	2017	MLP + GMF	Nonlinear Interaction
Hybrid CTR	2019	Deep + Factorization	Feature Interaction
LightGCN	2020	Graph	Simplification
Context-Aware	2020	Embedding	Personalization
Self-Attention	2021	Transformer	Sequential Modeling

Datasets and Evaluation Metrics

Study	Datasets	Metrics
Wide & Deep	Google Play	AUC
NCF	MovieLens, Pinterest	HR, NDCG
Hybrid CTR	Criteo, Avazu	LogLoss, AUC
LightGCN	Yelp, Amazon	Recall, NDCG
Context-Aware	Frappe, Last.fm	Precision, Recall
Self-Attention	Amazon, Steam	MRR, Recall

References

- Cheng, H.-T., Koc, L., Harmsen, J., Shaked, T., Chandra, T., Aradhye, H., Anderson, G., Corrado, G., Fu, W., & Shah, H. (2016). Wide & Deep Learning for Recommender Systems. <https://arxiv.org/abs/1606.07792>
- He, X., Liao, L., Zhang, H., Nie, L., Hu, X., & Chua, T.-S. (2017). Neural Collaborative Filtering. <https://arxiv.org/abs/1708.05031>
- Al-Hindy, A., Al-Sayid, B., & Al-Ani, A. (2019). A Hybrid Deep Learning Architecture for CTR Prediction. <https://ieeexplore.ieee.org/document/8954722>
- He, X., Deng, K., Wang, X., Li, Y., Zhang, Y., & Wang, M. (2020). LightGCN: Simplifying and Powering Graph Convolution Network for Recommendation. <https://arxiv.org/abs/2002.02126>
- Al-Yafi, H., Galland, A., & Gaussier, E. (2020). Deep Learning-Based Context-Aware Recommendation System. https://link.springer.com/chapter/10.1007/978-3-030-63007-2_40
- Al-Kasem, R., & Shahrour, G. (2021). Sequential Recommendation via Multi-Layer Self-Attention. <https://www.researchgate.net/publication/353957018>