

Student Name: Aseel Alwesabi

<https://www.kaggle.com/datasets/valakhorasani/mobile-device-usage-and-user-behavior-dataset>

```
import warnings
warnings.filterwarnings("ignore")
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns
from sklearn.model_selection import train_test_split
from sklearn.pipeline import Pipeline
from sklearn.preprocessing import StandardScaler, MinMaxScaler, LabelEncoder
from sklearn.feature_selection import SelectKBest, chi2, RFE
from sklearn.linear_model import LogisticRegression
from sklearn.tree import DecisionTreeClassifier
from sklearn.ensemble import RandomForestClassifier
from sklearn.svm import SVC
from sklearn.naive_bayes import GaussianNB
from sklearn.neighbors import KNeighborsClassifier
from sklearn.metrics import ( confusion_matrix, accuracy_score, precision_score, recall_score, f1_score, classification_report )

from imblearn.over_sampling import RandomOverSampler, SMOTE
from imblearn.under_sampling import RandomUnderSampler
from imblearn.combine import SMOTETomek
from sklearn.impute import SimpleImputer
from sklearn.model_selection import GridSearchCV
```

```
from google.colab import files

uploaded = files.upload()

for fn in uploaded.keys():
    print('User uploaded file "{name}" with length {length} bytes'.format(
        name=fn, length=len(uploaded[fn])))
```

No file chosen Upload widget is only available when the cell has been executed in the current browser session. Please rerun this cell to enable.
Saving user_behavior_dataset.csv to user_behavior_dataset.csv
User uploaded file "user_behavior_dataset.csv" with length 38878 bytes

```
df = pd.read_csv("user_behavior_dataset.csv")
df.head()
```

	User ID	Device Model	Operating System	App Usage Time (min/day)	Screen On Time (hours/day)	Battery Drain (mAh/day)	Number of Apps Installed	Data Usage (MB/day)	Age	Gender	User Behavior Class
0	1	Google Pixel 5	Android	393	6.4	1872	67	1122	40	Male	4
1	2	OnePlus 9	Android	268	4.7	1331	42	944	47	Female	3
2	3	Xiaomi Mi 11	Android	154	4.0	761	32	322	42	Male	2
3	4	Google Pixel 5	Android	239	4.8	1676	56	871	20	Male	3
4	5	iPhone 12	iOS	187	4.3	1367	58	988	31	Female	3

```
df['Device Model'].value_counts()

count
Device Model
Xiaomi Mi 11    146
iPhone 12       146
Google Pixel 5  142
OnePlus 9       133
Samsung Galaxy S21 133

dtype: int64
```

Getting the count of missing values

```
df.isnull().sum()

0
User ID      0
Device Model  0
Operating System  0
App Usage Time (min/day)  0
Screen On Time (hours/day)  0
Battery Drain (mAh/day)  0
Number of Apps Installed  0
Data Usage (MB/day)  0
Age          0
Gender       0
User Behavior Class  0

dtype: int64
```

Deleting columns that have 30% missing values

```
missing_percentage = df.isnull().mean()*100
Threshold = 30

columns_to_drop = missing_percentage[missing_percentage > Threshold].index
df = df.drop(columns=columns_to_drop)

print(f"Columns dropped: {list(columns_to_drop)}")
print (f"Remaining columns: {df.columns}")

Columns dropped: []
Remaining columns: Index(['User ID', 'Device Model', 'Operating System',
                          'App Usage Time (min/day)', 'Screen On Time (hours/day)',
                          'Battery Drain (mAh/day)', 'Number of Apps Installed',
                          'Data Usage (MB/day)', 'Age', 'Gender', 'User Behavior Class'],
                          dtype='object')
```

Detect Outliers

```
data = df.copy()
def detect_outliers_iqr(column):
    Q1 = column.quantile(0.25)
    Q3 = column.quantile(0.75)
    IQR = Q3 - Q1
    lower_bound = Q1 - 1.5 * IQR
    upper_bound = Q3 + 1.5 * IQR
    # Return a boolean series indicating if the value is an outlier
    return (column < lower_bound) | (column > upper_bound)

# Apply the IQR method to each numeric feature in the DataFrame
numeric_cols = data.select_dtypes(include=np.number).columns
for col in numeric_cols:
    data[f'{col}_Outlier'] = detect_outliers_iqr(data[col])

# Filter the DataFrame to display rows where any outlier flag is True
outliers_only = data[data.filter(like='_Outlier').any(axis=1)]
```


Display the filtered DataFrame with outliers

outliers_only

User ID	Device Model	Operating System	App Usage Time (min/day)	Screen On Time (hours/day)	Battery Drain (mAh/day)	Number of Apps Installed	Data Usage (MB/day)	Age	Gender	User Behavior Class	User_ID_Outlier	App Usage Time (min/day)_Outlier	Screen On Time (hours/day)_Outlier	Battery Drain (mAh/day)_Outlier	Number of Apps Installed_Outlier	Data Usage (MB/day)_Outlier	Age_Outlier	User Behavior Class_Outlier
---------	--------------	------------------	--------------------------	----------------------------	-------------------------	--------------------------	---------------------	-----	--------	---------------------	-----------------	----------------------------------	------------------------------------	---------------------------------	----------------------------------	-----------------------------	-------------	-----------------------------

Visualize Outliers

```
plt.figure(figsize=(12, 6))
for i, col in enumerate(df.columns[:3]): # Only plotting the first 3 features
    plt.subplot(1, 3, i+1) # Create subplots for each feature
    sns.boxplot(x=df[col])
    plt.title(f'Boxplot for {col}')
plt.tight_layout()
plt.show()
```



Handling Outliers

```
data=df.copy()
def replace_outliers_with_nan(column):
    Q1 = column.quantile(0.25)
    Q3 = column.quantile(0.75)
    IQR = Q3 - Q1
    lower_bound = Q1 - 1.5 * IQR
    upper_bound = Q3 + 1.5 * IQR
    # Replace outliers with NaN
    return column.where((column >= lower_bound) & (column <=
    upper_bound), np.nan)
# Replace outliers with NaN for each feature
numeric_cols = data.select_dtypes(include=np.number).columns
for col in numeric_cols:
    data[col] = replace_outliers_with_nan(data[col])
null_counts = data.isnull().sum()
print("Sum of null values in each column:")
print(null_counts)
```

```
Sum of null values in each column:
User ID      0
Device Model 0
Operating System 0
App Usage Time (min/day) 0
Screen On Time (hours/day) 0
Battery Drain (mAh/day) 0
Number of Apps Installed 0
Data Usage (MB/day) 0
Age 0
Gender 0
User Behavior Class 0
dtype: int64
```

Convert categorical features to numerical data

```
label_encoders = {}
for column in data.select_dtypes(include=['object']).columns:
    le = LabelEncoder()
    data[column] = le.fit_transform(data[column])
    label_encoders[column] = le
```

Median

```
X = data.select_dtypes(include=np.number).copy()

imputer = SimpleImputer(strategy='median')
X_imputed_array = imputer.fit_transform(X)

# Convert the imputed array back to a DataFrame
X = pd.DataFrame(X_imputed_array, columns=X.columns, index=X.index)

print(X)
```

```
User ID Device Model Operating System App Usage Time (min/day) \
0      1.0      0.0      0.0      393.0
1      2.0      1.0      0.0      268.0
2      3.0      3.0      0.0      154.0
3      4.0      0.0      0.0      239.0
4      5.0      4.0      1.0      187.0
..      ...      ...      ...      ...
695    696.0      4.0      1.0      92.0
696    697.0      3.0      0.0      316.0
697    698.0      0.0      0.0      99.0
698    699.0      2.0      0.0      62.0
699    700.0      1.0      0.0      212.0

Screen On Time (hours/day) Battery Drain (mAh/day) \
0      6.4      1872.0
1      4.7      1331.0
2      4.0      761.0
3      4.8      1676.0
4      4.3      1367.0
..      ...      ...
695      3.9      1082.0
696      6.8      1965.0
697      3.1      942.0
698      1.7      431.0
699      5.4      1306.0

Number of Apps Installed Data Usage (MB/day) Age Gender \
0      67.0      1122.0 40.0 1.0
1      42.0      944.0 47.0 0.0
2      32.0      322.0 42.0 1.0
3      56.0      871.0 20.0 1.0
4      58.0      908.0 31.0 0.0
..      ...      ...      ...
695      26.0      381.0 22.0 1.0
696      68.0      1201.0 59.0 1.0
697      22.0      457.0 50.0 0.0
698      13.0      224.0 44.0 1.0
699      49.0      828.0 23.0 0.0

User Behavior Class
0      4.0
1      3.0
```

2	2.0
3	3.0
4	3.0
...	...
695	2.0
696	4.0
697	2.0
698	1.0
699	3.0
[700 rows x 11 columns]	

df.describe()										
	User ID	App Usage Time (min/day)	Screen On Time (hours/day)	Battery Drain (mAh/day)	Number of Apps Installed	Data Usage (MB/day)	Age	User Behavior	Class	
count	700.00000	700.000000	700.000000	700.000000	700.000000	700.000000	700.000000	700.000000	700.000000	
mean	350.50000	271.128571	5.272714	1525.158571	50.681429	929.742857	38.482857		2.990000	
std	202.21688	177.199484	3.068584	819.136414	26.943324	640.451729	12.012916		1.401476	
min	1.00000	30.000000	1.000000	302.000000	10.000000	102.000000	18.000000		1.000000	
25%	175.75000	113.250000	2.500000	722.250000	26.000000	373.000000	28.000000		2.000000	
50%	350.50000	227.500000	4.900000	1502.500000	49.000000	823.500000	38.000000		3.000000	
75%	525.25000	434.250000	7.400000	2229.500000	74.000000	1341.000000	49.000000		4.000000	
max	700.00000	598.000000	12.000000	2993.000000	99.000000	2497.000000	59.000000		5.000000	

```
Split data into training and testing sets


X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.30 , random_state= 42 , stratify= y)
```

```
def evaluate_model(model_name, y_true, y_pred): # Calculate metrics
    accuracy = accuracy_score(y_true, y_pred)
    precision = precision_score(y_true, y_pred, average='weighted')
    recall = recall_score(y_true, y_pred, average= 'weighted')
    f1 = f1_score(y_true, y_pred, average= 'weighted')
    cm = confusion_matrix(y_true, y_pred)

    # Create a report
    report = classification_report(y_true, y_pred)
    # Output results
    metrics = {
        'Model Name' : model_name,
        'Accuracy' : accuracy,
        'Precision' : precision,
        'Recall': recall,
        'F1 Score': f1,
        'Classification Report': report    }

    # Plot Confusion Matrix
    plt.figure(figsize=(4, 4))
    sns.heatmap(cm, annot=True, fmt='d', cmap='Blues', cbar=False,
                xticklabels=np.unique(y_true), yticklabels=np.unique(y_true))
    plt.title(f'Confusion Matrix for {model_name}')
    plt.xlabel('Predicted Label')
    plt.ylabel('True Label')
    plt.show()
    return metrics
```

Average App Usage Time based on Device Model




```
Distribution of Users by Device Model

Device_Model = df['Device Model'].value_counts()
plt.figure(figsize=(6,6))
plt.pie(Device_Model, labels=Device_Model.index, autopct='%1.1f%%', startangle=90)
plt.title('Distribution of Users by Device Model')
plt.show()
```



```
Device Model Distribution by Gender


sns.countplot(x='Device Model', hue='Gender', data=df)
plt.title('Device Model Distribution by Gender')
plt.xlabel('Device Model')
plt.ylabel('Count')
plt.show()
```



Device Model Distribution by Age


```
def age_group(age):
    if age < 20:
        return "<20"
    elif age < 25:
        return "20-24"
    elif age < 40:
        return "25-39"
    else:
        return "40+"

df["Age_Group"] = df["Age"].apply(age_group)
plt.figure(figsize=(6,4))
sns.countplot(data=df, x='Device Model', hue='Age_Group', palette='Set1')
plt.title("Device Model Distribution by Age")
plt.show()
```




Device Model by User Behavior Class

```
sns.boxplot(x='Device Model', y='User Behavior Class', data=df)
plt.title("Device Model by User Behavior Class")
plt.xticks(rotation=45)
plt.xlabel('Device Model')
plt.ylabel('User Behavior Class')
plt.show()
```



Device Model by Number of Apps Installed


```
sns.boxplot(x='Device Model', y='Number of Apps Installed', data=df)
plt.title("Device Model by Number of Apps Installed")
plt.xticks(rotation=45)
plt.xlabel('Device Model')
plt.ylabel('Number of Apps Installed')
plt.show()
```



Random Forest Classifier

```
rf_classifier = RandomForestClassifier(n_estimators=100, random_state=42)
# Train the model
rf_classifier.fit(X_train, y_train)
# Make predictions
y_pred = rf_classifier.predict(X_test)
# Evaluate the model
evaluation_results = evaluate_model('RandomForestClassifier', y_test, y_pred)
# Print the evaluation results
for key, value in evaluation_results.items():
    if key == 'Classification Report':
        print(value) # Print report separately for better readability
    else:
        print(f"{key}: {value:.4f}" if isinstance(value, float) else
              f"{key}: {value}")
```

Confusion Matrix for RandomForestClassifier




Model Name:				
RandomForestClassifier				
Accuracy: 0.4357				
Precision: 0.4489				
Recall: 0.4357				
F1 Score: 0.4356				
	precision	recall	f1-score	support
0	0.28	0.26	0.27	58
1	0.23	0.29	0.25	48
2	0.28	0.32	0.30	50
3	0.32	0.23	0.27	61
4	1.00	1.00	1.00	63
accuracy			0.44	280
macro avg	0.42	0.42	0.42	280
weighted avg	0.44	0.44	0.44	280

Random Forest Classifier with grid search

```
from sklearn.model_selection import GridSearchCV
# Define the Random Forest Classifier
rf_classifier = RandomForestClassifier(random_state=42)
# Define the hyperparameters for grid search
param_grid = {
    'n_estimators': [100, 200, 300],
    'max_depth': [None, 10, 20, 30],
    'min_samples_split': [2, 5, 10],
    'min_samples_leaf': [1, 2, 4]
}
# Initialize GridSearchCV
grid_search = GridSearchCV(estimator=rf_classifier, param_grid=param_grid, cv=5, scoring='accuracy', n_jobs=-1)
# Fit the grid search to the data
grid_search.fit(X_train, y_train)
# Get the best estimator from grid search
best_rf_classifier = grid_search.best_estimator_
# Make predictions using the best model
y_pred = best_rf_classifier.predict(X_test)
# Evaluate the model
evaluation_results = evaluate_model('RandomForestClassifier', y_test, y_pred)
# Print the evaluation results
for key, value in evaluation_results.items():
    if key == 'Classification Report':
        print(value)
    else:
        print(f"{key}: {value:.4f}" if isinstance(value, float) else f"{key}: {value}")
# Print the best parameters found by grid search
print("\nBest hyperparameters found by GridSearchCV:")
print(grid_search.best_params_)
```

Confusion Matrix for RandomForestClassifier



Model Name:				
RandomForestClassifier				
Accuracy: 0.4214				
Precision: 0.4212				
Recall: 0.4214				
F1 Score: 0.4183				
	precision	recall	f1-score	support
0	0.26	0.24	0.25	58
1	0.21	0.27	0.24	48
2	0.29	0.36	0.32	50
3	0.24	0.16	0.20	61
4	1.00	1.00	1.00	63
accuracy			0.42	280
macro avg	0.40	0.41	0.40	280
weighted avg	0.42	0.42	0.42	280

Best hyperparameters found by GridSearchCV:
{ 'max_depth': None, 'min_samples_leaf': 2, 'min_samples_split': 5, 'n_estimators': 200 }


There isn't a huge difference between the Random Forest Classifier with and without Grid

Logistic Regression

```
LR = LogisticRegression()
# Train the model
LR.fit(X_train, y_train)
# Make predictions
y_pred = LR.predict(X_test)
# Evaluate the model
evaluation_results = evaluate_model('LogisticRegression', y_test, y_pred)
# Print the evaluation results
for key, value in evaluation_results.items():
    if key == 'Classification Report':
        print(value)
```

```
else:
    print(f"{key}: {value:.4f}" if isinstance(value, float) else f"{key}: \n{value}")
```

Confusion Matrix for LogisticRegression




Model Name:				
LogisticRegression				
Accuracy: 0.1929				
Precision: 0.1944				
Recall: 0.1929				
F1 Score: 0.1717				
	precision	recall	f1-score	support
0	0.19	0.47	0.27	58
1	0.16	0.15	0.15	48
2	0.14	0.04	0.06	50
3	0.27	0.16	0.20	61
4	0.20	0.13	0.15	63
accuracy			0.19	280
macro avg	0.19	0.19	0.17	280
weighted avg	0.19	0.19	0.17	280

Decision TreeClassifier

```
DT = DecisionTreeClassifier()
# Train the model
DT.fit(X_train, y_train)
# Make predictions
y_pred = DT.predict(X_test)
# Evaluate the model
evaluation_results = evaluate_model('DecisionTreeClassifier', y_test, y_pred) # Print the evaluation results
for key, value in evaluation_results.items():
    if key == 'Classification Report':
        print(value)
else:
    print(f"{key}: {value:.4f}" if isinstance(value, float) else f"{key}: \n{value}")
```

Confusion Matrix for DecisionTreeClassifier



Model Name:				
DecisionTreeClassifier				
Accuracy: 0.3893				
Precision: 0.3934				
Recall: 0.3893				
F1 Score: 0.3906				
	precision	recall	f1-score	support
0	0.23	0.21	0.22	58
1	0.16	0.21	0.18	48
2	0.16	0.16	0.16	50
3	0.29	0.26	0.28	61
4	1.00	1.00	1.00	63
accuracy			0.39	280
macro avg	0.37	0.37	0.37	280
weighted avg	0.39	0.39	0.39	280

Decision TreeClassifier with grid search

```
# Define the Decision Tree model
DT = DecisionTreeClassifier(random_state=42)
# Define the hyperparameters for grid search
param_grid = {
    'criterion': ['gini', 'entropy'],          # The function to measure the quality of a split
    'max_depth': [None, 10, 20, 30],          # The maximum depth of the tree
    'min_samples_split': [2, 5, 10],           # The minimum number of samples required to split an internal node
    'min_samples_leaf': [1, 2, 4],             # The minimum number of samples required to be at a leaf node
    'max_features': [None, 'sqrt', 'log2']     # The number of features to consider when looking for the best split
}
# Initialize GridSearchCV
grid_search = GridSearchCV(estimator=DT, param_grid=param_grid, cv=5, scoring='accuracy', n_jobs=-1)
# Fit the grid search to the data
grid_search.fit(X_train, y_train)
# Get the best estimator from grid search
best_DT = grid_search.best_estimator_
# Make predictions using the best model
y_pred = best_DT.predict(X_test)
# Evaluate the model
evaluation_results = evaluate_model('DecisionTreeClassifier', y_test, y_pred)
# Print the evaluation results
for key, value in evaluation_results.items():
    if key == 'Classification Report':
        print(value)
    else:
        print(f"{key}: {value:.4f}" if isinstance(value, float) else f"{key}: \n{value}")
# Print the best hyperparameters found by grid search
print("\nBest hyperparameters found by GridSearchCV:")
print(grid_search.best_params_)
```

Confusion Matrix for DecisionTreeClassifier

0

7

5

7

11

0

1

16

12

8

10

0

2

12

7

8

10

0

3

21

12

8

11

0

4

0

0

0

0

45

0

1

2

3

4

True Label

Predicted Label

Model Name:
DecisionTreeClassifier

Best hyperparameters found by GridSearchCV:
{'criterion': 'entropy', 'max_depth': None, 'max_features': None, 'min_samples_leaf': 2, 'min_samples_split': 10}
Accuracy: 0.3952

Best hyperparameters found by GridSearchCV:
{'criterion': 'entropy', 'max_depth': None, 'max_features': None, 'min_samples_leaf': 2, 'min_samples_split': 10}
Precision: 0.4155

Best hyperparameters found by GridSearchCV:
{'criterion': 'entropy', 'max_depth': None, 'max_features': None, 'min_samples_leaf': 2, 'min_samples_split': 10}
Recall: 0.3952

Best hyperparameters found by GridSearchCV:
{'criterion': 'entropy', 'max_depth': None, 'max_features': None, 'min_samples_leaf': 2, 'min_samples_split': 10}
F1 Score: 0.4011

Best hyperparameters found by GridSearchCV:
{'criterion': 'entropy', 'max_depth': None, 'max_features': None, 'min_samples_leaf': 2, 'min_samples_split': 10}

precision

recall

f1-score

support

0

0.12

0.23

0.16

30

1

0.33

0.26

0.29

46

2

0.26

0.22

0.24

37

3

0.26

0.21

0.23

52

4

1.00

1.00

1.00

45

accuracy

0.40

210

macro avg

0.40

0.38

0.38

210

weighted avg


0.42

0.40

0.40

210

Chi-Square



Comparison of models using features selected by the Chi-Square test

X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.40, random_state=40)
k = 10
selector = SelectKBest(score_func=chi2, k=k)
X_train_k = selector.fit_transform(X_train, y_train)
X_test_k = selector.transform(X_test)
selected_features = X.columns[selector.get_support(indices=True)]
print("Selected Features:", list(selected_features))

models = { "Random Forest": RandomForestClassifier(n_estimators=200, random_state=42),
 "Decision Tree": DecisionTreeClassifier(random_state=42),
 "SVM": SVC(kernel='rbf', random_state=42)}

metrics = []

for name, model in models.items():
 model.fit(X_train_k, y_train)
 y_pred = model.predict(X_test_k)
 print(f"\n==== Classification Report: {name} =====")
 print(classification_report(y_test, y_pred))

 metrics.append({
 "Model": name,
 "Accuracy": accuracy_score(y_test, y_pred),
 "Precision": precision_score(y_test, y_pred,
 average='weighted'),
 "Recall": recall_score(y_test, y_pred, average='weighted') })

results_df = pd.DataFrame(metrics)
print("\nModel Performance:")
print(results_df)

Selected Features: ['User ID', 'Operating System', 'App Usage Time (min/day)', 'Screen On Time (hours/day)', 'Battery Drain (mAh/day)', 'Number of Apps Installed', 'Data Usage (MB/day)', 'Age', 'Gender', 'User Behavior Class']

==== Classification Report: Random Forest =====
precision recall f1-score support
0 0.27 0.26 0.26 58
1 0.23 0.29 0.26 48
2 0.30 0.30 0.30 50
3 0.26 0.21 0.23 61

4	1.00	1.00	1.00	63
accuracy			0.43	280
macro avg	0.41	0.41	0.41	280
weighted avg	0.43	0.43	0.43	280

Model Performance:				
	Model	Accuracy	Precision	Recall
0	Random Forest	0.428571	0.430043	0.428571
==== Classification Report: Decision Tree ====				
	precision	recall	f1-score	support
0	0.24	0.21	0.22	50
1	0.16	0.21	0.18	48
2	0.15	0.14	0.14	50
3	0.29	0.28	0.28	61
4	1.00	1.00	1.00	63
accuracy			0.39	280
macro avg	0.37	0.37	0.37	280
weighted avg	0.39	0.39	0.39	280


Model Performance:				
	Model	Accuracy	Precision	Recall
0	Random Forest	0.428571	0.430043	0.428571
1	Decision Tree	0.389286	0.392747	0.389286
==== Classification Report: SVM ====				
	precision	recall	f1-score	support
0	0.19	0.55	0.28	50
1	0.00	0.00	0.00	48
2	0.00	0.00	0.00	50
3	0.18	0.11	0.14	61
4	0.21	0.24	0.22	63
accuracy			0.19	280
macro avg	0.12	0.18	0.13	280
weighted avg	0.12	0.19	0.14	280

Model Performance:				
	Model	Accuracy	Precision	Recall
0	Random Forest	0.428571	0.430043	0.428571
1	Decision Tree	0.389286	0.392747	0.389286
2	SVM	0.192857	0.124791	0.192857

Recursive Feature Elimination (RFE) with Logistic Regression

```
model = LogisticRegression(max_iter=500)
rfe = RFE(model, n_features_to_select=10)
rfe.fit(X, y)

feature_ranking = pd.DataFrame({
    'Feature': X.columns,
    'Ranking': rfe.ranking_})
feature_ranking = feature_ranking.sort_values(by='Ranking', ascending=True)
plt.figure(figsize=(10, 6))
plt.bar(feature_ranking['Feature'], feature_ranking['Ranking'])
plt.xlabel("Feature")
plt.ylabel("RFE Ranking (1 = Selected)")
plt.title("RFE Feature Ranking")
plt.xticks(rotation=90)
plt.tight_layout()
plt.show()
```



Comparison of models using features selected by the REF

```
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.30, random_state=42)
model = LogisticRegression(max_iter=500)
rfe = RFE(model, n_features_to_select=10)
rfe.fit(X, y)
X_train_k = rfe.fit_transform(X_train, y_train)
X_test_k = rfe.transform(X_test)
selected_features = X.columns[rfe.get_support(indices=True)]
print("Selected Features:", list(selected_features))

models = { "Random Forest": RandomForestClassifier(n_estimators=200, random_state=42),
           "Decision Tree": DecisionTreeClassifier(random_state=42),
           "SVM": SVC(kernel='rbf', random_state=42)}

metrics = []

for name, model in models.items():
    model.fit(X_train_k, y_train)
    y_pred = model.predict(X_test_k)
    print(f"\n==== Classification Report: {name} =====")
    print(classification_report(y_test, y_pred))
    metrics.append({ "Model": name, "Accuracy": accuracy_score(y_test, y_pred),
                    "Precision": precision_score(y_test, y_pred, average='weighted'),
                    "Recall": recall_score(y_test, y_pred, average='weighted') })

results_df = pd.DataFrame(metrics)
print("\nModel Performance:")
print(results_df)
```

Selected Features: ['User ID', 'Operating System', 'App Usage Time (min/day)', 'Screen On Time (hours/day)', 'Battery Drain (mAh/day)', 'Number of Apps Installed', 'Age', 'Gender', 'User Behavior Class', 'Age_Group']

==== Classification Report: SVM ====				
	precision	recall	f1-score	support
0	0.14	1.00	0.25	30
1	0.00	0.00	0.00	46
2	0.00	0.00	0.00	37
3	0.00	0.00	0.00	52
4	0.00	0.00	0.00	45
accuracy			0.14	210
macro avg	0.03	0.20	0.05	210
weighted avg	0.02	0.14	0.04	210

Model Performance:				
	Model	Accuracy	Precision	Recall
0	SVM	0.142857	0.020408	0.142857

Train Random Forest

```
rf = RandomForestClassifier(random_state=42)
rf.fit(X, y)


importances = rf.feature_importances_

feature_names = X.columns if hasattr(X, "columns") else [f"Feature {i}"
                                                         for i in range(X.shape[1])]

df_importance = pd.DataFrame({ 'Feature': feature_names, 'Importance': importances})

df_importance = df_importance.sort_values(by='Importance', ascending=False)

plt.figure(figsize=(10, 6))
plt.barh(df_importance['Feature'][::-1],
         df_importance['Importance'][::-1])
plt.xlabel('Feature Importance')
plt.title('Random Forest Feature Importance')
plt.tight_layout()
plt.show()
```



```
from sklearn.preprocessing import LabelEncoder
label_encoders = {}
for column in df.select_dtypes(include=['object']).columns:
    le = LabelEncoder()
    df[column] = le.fit_transform(df[column])
    label_encoders[column] = le
plt.figure(figsize=(20, 16))
sns.heatmap(df.corr(), annot=True, cmap='coolwarm')
plt.title('Correlation Heatmap')
plt.show()
```

