

Deep Learning & Neural Networks

Dr. Shahira Ahmed

DS710

Lecture 3





Faculty of Engineering
جامعة ميدوcean
المدينة التعليمية

Deep Learning & Neural Networks

DS710

Lecture 3
Training the Network-Part(1)


- Linear Algebra Review
- What is Vectorization?
- How Vectorization is important in Machine learning?
- Advantages of Vectorized Implementation
- Demonstration on Colab
- Representing Neural Network weighted sum as vectors
- Training Network

- Scalars is only a Single numbers
- Vectors: A vector is an array of numbers

$$\mathbf{x} = \begin{bmatrix} x_1 \\ x_2 \\ \dots \\ x_n \end{bmatrix}$$

- Matrix:
$$\mathbf{A} = \begin{bmatrix} A_{1,1} & A_{1,2} & \dots & A_{1,n} \\ A_{2,1} & A_{2,2} & \dots & A_{2,n} \\ \dots & \dots & \dots & \dots \\ A_{m,1} & A_{m,2} & \dots & A_{m,n} \end{bmatrix}$$

- A tensor is a n-dimensional array with $n > 2$



Grayscale Image


6 x 6



6 x 6

1	0	4	2	125	67
8	2	5	4	34	12
20	13	25	15	240	2
76	8	6	6	100	76
34	66	134	223	201	3
255	123	89	55	32	2

<https://dev.to/sandeepbalachandran/machine-learning-going-further-with-cnn-part-2-41km>




<https://dev.to/sandeepbalachandran/machine-learning-going-further-with-cnn-part-2-41km>

Linear Algebra Review



RGB Image




<https://dev.to/sandeepbalachandran/machine-learning-going-further-with-cnn-part-2-41km>

RGB Image

5 x 5 x 3



3D Array



<https://dev.to/sandeepbalachandran/machine-learning-going-further-with-cnn-part-2-41km>


Linear Algebra Review

(11)


SCALAR




Row Vector
(shape 1x3)



Column Vector
(shape 3x1)



MATRIX



TENSOR

<https://dev.to/mmithrakumar/scalars-vectors-matrices-and-tensors-with-tensorflow-2-0-1f66>

- An algebraic operation in which two equal length vectors are being multiplied such that it produces a single number. Dot Product often called as inner product. This product results in a scalar number

$$a \cdot b = \begin{bmatrix} a_1 & a_2 & a_3 & a_4 & a_5 \end{bmatrix}_{(1 \times n)} \begin{bmatrix} b_1 \\ b_2 \\ b_3 \\ b_4 \\ b_5 \end{bmatrix}_{(n \times 1)} = \left\{ a_1b_1 + a_2b_2 + a_3b_3 + a_4b_4 + a_5b_5 \right\}$$

Dot Product

Dot Product

$$\begin{bmatrix} 1 & 2 \\ 3 & 4 \end{bmatrix} \cdot \begin{bmatrix} 5 & 6 \\ 7 & 8 \end{bmatrix} = \begin{bmatrix} (1 \cdot 5) + (2 \cdot 7) & (1 \cdot 6) + (2 \cdot 8) \\ (3 \cdot 5) + (4 \cdot 7) & (3 \cdot 6) + (4 \cdot 8) \end{bmatrix}$$
$$= \begin{bmatrix} 5 + 14 & 6 + 16 \\ 15 + 28 & 18 + 32 \end{bmatrix} = \begin{bmatrix} 19 & 22 \\ 43 & 50 \end{bmatrix}$$

- Multiply two vectors a and b with dimension $n \times 1$ and $m \times 1$ then the outer product of the vector results in a rectangular matrix of $n \times m$.

$$a \otimes b = ab^T = \begin{bmatrix} a_1 \\ a_2 \\ a_3 \\ a_4 \\ a_5 \end{bmatrix}_{(n \times 1)} \begin{bmatrix} b_1 & b_2 & b_3 & b_4 & b_5 \end{bmatrix}_{(1 \times n)} = \begin{Bmatrix} a_1b_1 & a_1b_2 & a_1b_3 & a_1b_4 & a_1b_5 \\ a_2b_1 & a_2b_2 & a_2b_3 & a_2b_4 & a_2b_5 \\ a_3b_1 & a_3b_2 & a_3b_3 & a_3b_4 & a_3b_5 \\ a_4b_1 & a_4b_2 & a_4b_3 & a_4b_4 & a_4b_5 \\ a_5b_1 & a_5b_2 & a_5b_3 & a_5b_4 & a_5b_5 \end{Bmatrix}_{(n \times n)}$$

Outer Product

Element-wise multiplication of two matrices is the algebraic operation in which each element of first matrix is multiplied by its corresponding element in the later matrix. Dimension of the matrices should be same.

$$a \circ b = \begin{bmatrix} a_1 \\ a_2 \\ a_3 \\ a_4 \\ a_5 \end{bmatrix}_{(n \times 1)} \circ \begin{bmatrix} b_1 \\ b_2 \\ b_3 \\ b_4 \\ b_5 \end{bmatrix}_{(n \times 1)} = \begin{bmatrix} a_1b_1 \\ a_2b_2 \\ a_3b_3 \\ a_4b_4 \\ a_5b_5 \end{bmatrix}_{(n \times 1)}$$

Element wise Product

Transpose

$$\begin{bmatrix} 1 & 2 & 3 \\ 4 & 5 & 6 \\ 7 & 8 & 9 \end{bmatrix}$$

Input


$$\begin{bmatrix} 1 & 4 & 7 \\ 2 & 5 & 8 \\ 3 & 6 & 9 \end{bmatrix}$$

Output

What is Vectorization?

- Vectorization in machine learning refers to the process of represents data into Vectors, Matrices, and Tensors.
- Process data without using loops


Why Vectorization



<https://medium.com/@jwbtfmf/vectorization-in-deep-learning-c47f0d171d0a>

Why Vectorization?

SIMD is short for Single Instruction/Multiple Data, while the term SIMD operations refer to a computing method that enables the processing of multiple data with a single instruction



<https://medium.com/@jwbtfmf/vectorization-in-deep-learning-c47f0d171d0a>

Why Vectorization?


- Efficiency : Due to the fact that they make use of the parallel processing capability of contemporary CPUs and GPUs, vectorized operations are often performed significantly quicker than their non-vectorized equivalents. This can lead to significant speed-ups in training and inference.
- Memory : Vectorized operations can also reduce memory usage.

Why Vectorization

- Express data as matrices
- Perform computations on multiple data points simultaneously
- Performing parallel computations using matrix operations
- Hardware accelerators like GPUs
- Efficient memory utilization
- Less Time- more speed


- **CPU (Central Processing Unit):**

- A CPU is the primary processing unit in a computer system. CPUs excel at sequential processing and are optimized for tasks that require high single-threaded performance. They are commonly found in desktop and laptop computers, servers, and mobile devices.




- <https://www.youtube.com/watch?v=-P28LKWTzrI>

- **TPU (Tensor Processing Unit):**
 - A TPU is a specialized application-specific integrated circuit (ASIC) developed by Google for accelerating machine learning workloads.
 - It is specifically designed to perform tensor operations, which are fundamental to many machine learning algorithms.
 - TPUs are highly optimized for matrix multiplication and are capable of delivering significantly higher performance compared to CPUs and GPUs for deep learning tasks.
 - They are commonly used in data centers and cloud computing platforms to accelerate machine learning training and inference.



TPU^{v4}

Recap: the perceptron




Linear vs Affine?

$$z = \sum_i w_i x_i + b$$

$$y = \begin{cases} 1 & \text{if } z \geq 0 \\ 0 & \text{else} \end{cases}$$




- – “Fires” if the affine function of inputs is positive

Recap: the perceptron




<https://towardsdatascience.com/perceptrons-the-first-neural-network-model-8b3ee4513757>

Recap : Nnets and the brain



- Neural nets are composed of networks of computational models of neurons called perceptrons


Learning the Network



Calculate Weights



<https://www.scaler.com/topics/machine-learning/perceptron-learning-algorithm/>

- (1) Calculate Weighted Sum: multiply all input values with corresponding weight values and then add them to determine the weighted sum. Mathematically, we can calculate the weighted sum as follows:
- $\sum w_i * x_i = x_1 * w_1 + x_2 * w_2 + \dots + w_m * x_m$. Add another term called bias 'b' to the weighted sum to improve the model performance.




$$= \sum_{i=0}^m w_i x_i$$


- (2) an activation function is applied to this weighed sum, producing a binary or a continuous-valued output. $Y = f(\sum_{i=0}^m w_i x_i)$



- (3) Evaluate
 - The difference between this output and the actual target value is computed to get the error term, E , generally in terms of mean squared error. The steps up to this form the forward propagation part of the algorithm $(\text{Predicted} - \text{Actual})^2$.



Perceptron learning algorithm



$w_1, w_2, w_3, \dots \dots \dots w_m$

Samples	Variables							
	Variable 1	Variable 2	Variable 3	Variable 4	Variable 5	Variable 6		Variable m
	Sample 1	29	31	34	36	39	48	48
	Sample 2	27	29	31	34	36	45	45
	Sample 3	25	27	29	31	34	42	42
	Sample 4	23	25	27	29	31	39	39
	...	...	...	...	...	...		...
Sample n	18	20	21	23	24	26		20

- The **dimensions** of a matrix give the number of rows and columns of the matrix *in that order*.

3 columns

↓ ↓ ↓

$$A = \begin{bmatrix} -2 & 5 & 6 \\ 5 & 2 & 7 \end{bmatrix}$$

← ← 2 rows

2*3
Matrix

Matrix Operation

$$A = \begin{bmatrix} 1 & 3 \\ 2 & 4 \\ 2 & 5 \end{bmatrix} \text{ and } B = \begin{bmatrix} 1 & 3 & 2 & 2 \\ 2 & 4 & 5 & 1 \end{bmatrix}$$

$$A = \begin{bmatrix} 1 & 3 \\ 2 & 4 \\ 2 & 5 \end{bmatrix} \text{ and } B = \begin{bmatrix} 1 & 3 & 2 & 2 \\ 2 & 4 & 5 & 1 \end{bmatrix}$$

2 row entries
= 2 columns



$$A = \begin{bmatrix} 1 & 3 \\ 2 & 4 \\ 2 & 5 \end{bmatrix}$$

2 column entries
= 2 rows



$$B = \begin{bmatrix} 1 & 3 & 2 & 2 \\ 2 & 4 & 5 & 1 \end{bmatrix}$$

$$(m \times n) \cdot (n \times k)$$



product is defined

Is CD defined?

$$C = \begin{bmatrix} 5 & 3 & 6 & 1 \\ 6 & 8 & 5 & 3 \end{bmatrix} \text{ and } D = \begin{bmatrix} 2 & 1 & 8 \\ 7 & 5 & 5 \end{bmatrix}.$$

CD Undefined

A is a 4×2 matrix and B is a 2×3 matrix.

- IS AB Defined?
- IS BA Defined?
- IS AB Defined?Yes
- IS BA Defined?NO

$w_1, w_2, w_3, \dots \dots \dots w_m$

$1 \times m$

Samples

Variables

	Variable 1	Variable 2	Variable 3	Variable 4	Variable 5	Variable 6		Variable m
Sample 1	29	31	34	36	39	48		48
Sample 2	27	29	31	34	36	45		45
Sample 3	25	27	29	31	34	42		42
Sample 4	23	25	27	29	31	39		39
...	...	...	...	...	...	...		...
Sample n	18	20	21	23	24	26		20

$n \times m$

Matrix Operations

$w_1, w_2, w_3, \dots \dots \dots w_m$

$1 \times m$

w_1
 w_2
 w_3

 w_m

$m \times 1$

Samples

Variables

	Variable 1	Variable 2	Variable 3	Variable 4	Variable 5	Variable 6		Variable m
Sample 1	29	31	34	36	39	48		48
Sample 2	27	29	31	34	36	45		45
Sample 3	25	27	29	31	34	42		42
Sample 4	23	25	27	29	31	39		39
...	...	...	...	...	...	...		...
Sample n	18	20	21	23	24	26		20


$n \times m$

- Weighted Sum

- $\sum_{i=1}^m w_i x_i + b$

- $\sum_{i=0}^m w_i x_i$

- $\mathbf{w}^T \mathbf{x}$






وزارة التعليم
Ministry of Education
الهيئة العامة للتعليم
العام



Learning the Network

- A perceptron model's output can only be a binary number i.e. “0” or “1” because of activation function.
- The perceptron model can only be used to categorize the input vectors' linearly separable sets. If input vectors are non-linear, they can't be properly classified.


The multi-layer perceptron



- A network of perceptrons
 - Perceptrons “feed” other perceptrons.


Option 1: Construct by hand

Assuming simple perceptrons:
output = 1 if $\sum_i w_i x_i + b_i \geq 0$, else 0




- Given a function, *handcraft* a network to satisfy it
- E.g.: Build an MLP to classify this decision boundary

Option 1: Construct by hand




- Given a function, *handcraft* a network to satisfy it
- E.g.: Build an MLP to classify this decision boundary

Option 1: Construct by hand




- Given a function, *handcraft* a network to satisfy it
- E.g.: Build an MLP to classify this decision boundary

Option 1: Construct by hand




- Given a function, *handcraft* a network to satisfy it
- E.g.: Build an MLP to classify this decision boundary

Option 1: Construct by hand



- Given a function, *handcraft* a network to satisfy it
- E.g.: Build an MLP to classify this decision boundary


Option 1: Construct by hand



<https://deeplearning.cs.cmu.edu/S23/>

Assuming simple perceptrons:
output = 1 if $\sum_i w_i x_i + b_i \geq 0$, else 0


Option 1: Construct by hand



<https://deeplearning.cs.cmu.edu/S23/>

Assuming simple perceptrons:
output = 1 if $\sum_i w_i x_i + b_i \geq 0$, else 0

Option 1: Construct by hand



- Given a function, *handcraft* a network to satisfy it
- E.g.: Build an MLP to classify this decision boundary
- **Not possible for all but the simplest problems..**

<https://deeplearning.cs.cmu.edu/S23/>

- Vectorization
- Advantages of Vectorized Implementation
- Single vs Multilayer perceptron
- Training Network by hand



مجموعة جامعة
الجميع الذكية
للتعليم القابضة

MIDOCEAN
UNIVERSITY
BY EVERYONE'S SMART UNIVERSITY

*Thank
you*



www.midocean.ae

