

```
> Frame 1: 28 bytes on wire (224 bits), 28 bytes captured (224 bits)
> Internet Protocol Version 4, Src: 10.0.0.7, Dst: 216.239.38.120
> Internet Control Message Protocol
```

```
0000 45 48 00 1c 00 01 00 00 40 01 71 2a 0a 00 00 07 EH.....@.q*...
0010 d8 ef 26 78 08 00 f7 c5 00 01 00 39 ..&x.....9
```

```
> Frame 79: 46 bytes on wire (368 bits), 46 bytes captured (368 bits) on interface \Device\NPF_{66DEBD7D-B40B-4B07-BF1A-44A6AEFC027C}, id 0
> Ethernet II, Src: Microsof_7f:0b:3d (b8:31:b5:7f:0b:3d), Dst: HewlettP_00:d0:a8 (00:23:7d:00:d0:a8)
▼ 802.1Q Virtual LAN, PRI: 3, DEI: 0, ID: 20
    011. .... = Priority: Critical Applications (3)
    ...0 .... = DEI: Ineligible
    .... 0000 0001 0100 = ID: 20
    Type: IPv4 (0x0800)
▼ Internet Protocol Version 4, Src: 192.168.0.2, Dst: 192.168.0.1
    0100 .... = Version: 4
    .... 0101 = Header Length: 20 bytes (5)
    > Differentiated Services Field: 0x48 (DSCP: AF21, ECN: Not-ECT)
        Total Length: 28
        Identification: 0x0001 (1)
    > Flags: 0x00
        ...0 0000 0000 0000 = Fragment Offset: 0
        Time to Live: 64
        Protocol: UDP (17)
        Header Checksum: 0xf934 [validation disabled]
        [Header checksum status: Unverified]
        Source Address: 192.168.0.2
        Destination Address: 192.168.0.1
> User Datagram Protocol, Src Port: 53, Dst Port: 53
```

0000	00 23 7d 00 d0 a8 b8 31 b5 7f 0b 3d 81 00 60 14	.#}...1..=..`.
0010	08 00 45 48 00 1c 00 01 00 00 40 11 f9 34 c0 a8	..EH....@..4..
0020	00 02 c0 a8 00 01 00 35 00 35 00 08 7e 20	5.5..~