



Network Programming in Python

Prepared by Dr. Hamada I. AbdulWakel

Lecture 3



The background features a series of vertical panels with rounded ends. The leftmost panel shows a person's hands typing on a laptop. The subsequent panels contain various white line-art icons on a semi-transparent background: a graduation cap, a play button, a target with an arrow, an open book, a magnifying glass, and a group of people. The title text is positioned to the right of these panels.

Basics of Network Programming – Part II

Lecture 3

Prepared by
Dr. Hamada I. AbdulWakel

www.midocean.edu.km

Lecture

03

RECAP: LECTURE 2

- Service Oriented Architecture (SOA).
- Application Program Interface (API).
- API modules in Python.

Lecture

03

LECTURE MAIN POINTS

- Application Program Interface (API).
- BeautifulSoup and web scraping.
- Socket Programming in Python.

GOOGLE MAPS API

- **Geocoding:** the process of converting human-readable addresses into geographic coordinates (i.e., latitude and longitude), which you can use to place markers on a map.
- **Reverse geocoding:** the process of converting geographic coordinates into a human-readable address.
- Map APIs allow you to create location-aware infographics, mind maps and visualization aids.

Lecture

03

GOOGLE MAPS API

Cont'd

Enter a query to geocode, or click on the map to reverse geocode.

Enter a location

[Show options](#)

The request did not encounter any errors (OK).

Found 1 results. ([view all in map](#)) [[JSON](#)] [[XML](#)] [[Collapse](#)]

Address: Mecca Saudi Arabia

Location: 21.389082,39.857912 (type: APPROXIMATE)

Types: locality, political

Address components:

locality	Mecca	political
	Makkah	
administrative_area_level_2	Makkah Principality	political
administrative_area_level_1	Makkah Province	political
country	Saudi Arabia	political
	SA	

Bounds: 21.279028,39.690235 – 21.593003,40.002858

Viewport: 21.279028,39.690235 – 21.593003,40.002858

Place ID: [ChIJdYeB7UwbwhURzslwz2kkq5g](#)

Map Satellite

Mecca مكة المكرمة

Google

Keyboard shortcuts Map data ©2023 Google 10 km Terms

Lecture

03

GOOGLE MAPS API

Cont'd

- Google map API simulation.
 - URL:
<https://py4e-data.dr-chuck.net/json?address=mecca&key=42>

```
py4e-data.dr-chuck.net/json?address=mecca&key=42
{
  - results: [
    - {
      - address_components: [
        - {
          long_name: "Mecca",
          short_name: "Makkah",
          + types: [ - ]
        },
        + { - },
        + { - },
        - {
          long_name: "Saudi Arabia",
          short_name: "SA",
          - types: [
            "country",
            "political"
          ]
        }
      ],
      formatted_address: "Mecca Saudi Arabia",
      - geometry: {
        - bounds: {
          - northeast: {
            lat: 21.5930031,
            lng: 40.0028579
          },
          - southwest: {
            lat: 21.2790277,
            lng: 39.6902353
          }
        },
        - location: {
          lat: 21.3890824,
          lng: 39.8579118
        }
      }
    }
  ]
}
```

Lecture

03

GOOGLE MAPS API

Cont'd

• Code:

```
import urllib.error, urllib.parse, urllib.request
import json
api_key = False
if api_key is False:
    api_key = 42
    serviceurl = 'http://py4e-data.dr-chuck.net/json?'
else:
    serviceurl = 'https://maps.googleapis.com/maps/api/geocode/json?'
```

Lecture

03

GOOGLE MAPS API

Cont'd

- Code:

```
while True:
    address = input("Enter location: ")
    if len(address) < 1:
        break
    parms = dict()
    parms['address'] = address
    if api_key is not False:
        parms['key'] = api_key
```

- Code (inside while loop):

```
url = serviceurl + urllib.parse.urlencode(parms)
print('Retrieving', url)
urllib_handler = urllib.request.urlopen(url)
data = urllib_handler.read().decode()
print('Retrieved', len(data), 'characters')
try:
    js = json.loads(data)
except:
    js = None
```

Lecture

03

GOOGLE MAPS API

Cont'd

- Code (inside while loop):

```
if 'status' not in js or js['status'] != 'OK':  
    print('Fail to retrieve data')  
    print(data)  
    continue  
print(json.dumps(js, indent=4))  
lat = js['results'][0]['geometry']['location']['lat']  
lng = js['results'][0]['geometry']['location']['lng']  
location = js['results'][0]['formatted_address']  
print('lat', lat, 'lng', lng, "location", location)
```

Lecture

03

WEB SCRAPING

- When a program pretends to be a web browser and retrieves web pages, extracts information, and then looks at more pages.
- Uses:
 - Monitor a site for new information.
 - Make a database for a search engine.
 - Get your data from a system that has no export feature.
 - Pull social data.


Lecture

03

BE CAREFUL WITH WEB SCRAPING

- There is some controversy about web scraping.
- Do not republishing copyrighted material.
- Do not violate terms of service.

Sorry, you have been blocked
You are unable to access youm7.com




Lecture

03

BEAUTIFULSOUP MODULE

```
<!DOCTYPE html>
<html>
  <head>
    <title></title>
  </head>
  <body>
    <h1></h1>
    <h1></h1>
  </body>
</html>
```



Lecture

03

BEAUTIFULSOUP MODULE

Cont'd

- **BeautifulSoup** is a Python module for pulling data out of HTML and XML files.
- One of the important pieces of HTML document are **tags**, which may contain other tags/strings (tag's children).
- BeautifulSoup provides different ways to navigate and iterate over these tags.
- BeautifulSoup is the object created when we try to **scrape a web resource**.

Lecture

03


INSTALLATION OF BEAUTIFULSOUP
MODULE

- Installation:
 - PyPi: `pip install beautifulsoup4`
- Beautiful Soup supports different HTML parser such as:
 - **Html.parser**: the default HTML parser included in Python's standard library.
 - lxml
 - `pip install lxml`
 - Html5lib
 - `pip install html5lib`

Lecture

03

WEB SCRAPING STEPS



WEB SCRAPING STEPS

Cont'd


- **Step 1: Inspect your data source:**
 - A manual step.
 - Open the website you want to pull important content from it.
 - Open inspection.
 - On Mac:
`Cmd+Alt+I`
 - On Windows/Linux:
`Ctrl+Shift+I`
 - Understand the website structure to know where these important data.

Lecture

03

WEB SCRAPING STEPS

Cont'd



The screenshot shows the PyPI page for BeautifulSoup4 4.12.2. The page has a blue header with a search bar and navigation links (Help, Sponsors, Log in, Register). Below the header, the title 'beautifulsoup4 4.12.2' is displayed, followed by a code block containing 'pip install beautifulsoup4'. A 'Screen-scraping library' banner is visible. On the left, a 'Navigation' sidebar lists 'Project description', 'Release history', and 'Download files'. The main content area includes a 'Project description' section and a 'Quick start' section. A browser context menu is open on the right side of the page, with a red arrow pointing to the 'View page source' option.

Search projects

Help Sponsors Log in Register

beautifulsoup4 4.12.2

```
pip install beautifulsoup4
```

Screen-scraping library

Navigation

- Project description
- Release history
- Download files

Project description

Beautiful Soup is a library that makes it easy to scrape information from web pages, using Pythonic idioms to navigate the tree structure of the parsed document. It provides Pythonic idioms for iterating, searching, and modifying the tree.

Quick start

- Back
- Forward
- Reload
- Save as...
- Print...
- Cast...
- Search images with Google
- Send to your devices
- Create QR Code for this page
- Translate to English
- Block element...
- Copy BibTeX to clipboard
- JSONVue
- View page source
- Inspect

Lecture

03

WEB SCRAPING STEPS

Cont'd

Project details

Release history

Download files

h2.page-title 593 x 61.91

Project description

Beautiful Soup is a library that makes it easy to scrape information from web pages. It sits atop an HTML or XML parser, providing Pythonic idioms for iterating, searching, and modifying the parse tree.

```

<!-- mobile menu -->
<nav aria-label="Navigation for beautifulso
up4">...</nav>
<div id="description" data-project-tabs-
target="content" class="vertical-tabs__cont
ent" role="tabpanel" aria-labelledby="descr
iption-tab mobile-description-tab"
tabindex="-1" style="display: block;">
...
<h2 class="page-title">Project
description</h2> == $0
<div class="project-description">...</div>
</div>
<div id="data" data-project-tabs-target="co
ntent" class="vertical-tabs__content" role=
"tabpanel" aria-labelledby="mobile-data-ta
b" tabindex="-1" style="display: none;">...
</div>
<div id="history" data-project-tabs-target=
"content" class="vertical-tabs__content"
role="tabpanel" aria-labelledby="history-ta

```

WEB SCRAPING STEPS

Cont'd

- **Step 2: Scrape HTML content from a page:**
 - Create the soup object.
 - Read the web page content using this object.
- **Step 3: Parse HTML code with BeautifulSoup:**
 - Parse the web page content to make it more accessible.
 - Pick out the data from the required HTML tags.

Lecture

03

BEAUTIFULSOUP MODULE METHODS

- **Beautifulsoup(content, parser):** creates a soup object.
- **soupObj.prettify():** gives the visual representation of the parsed URL. It arranges all the tags in a parse-tree manner with better readability.
- **soupObj.title:** gives the title tag with its content.
- **soupObj.title.string:** gives the title content only without the tag.

Lecture

03

**BEAUTIFULSOUP MODULE
METHODS**

Cont'd

- `soupObj.find("tagName")`: gives the first occurrence of the given tag name.
- `soupObj.find_all("tagName")`: gives a list of all occurrences of the given tag name with they contents.
 - `firstTag = soupObj.find_all("tagName")[0]`
 - If the firstTag contains other tags:
`firstTag.find_all("otherTagName")`

BEAUTIFULSOUP MODULE METHODS

Cont'd

- **soupObj.find_all("tagName", { css style })**: gives a list of all occurrences of the given tag name with they contents which have the same given css style.
- **tag.get("propertyName")**: gives the value of the given property for the selected tag.
- **tag.text**: gives the content of the selected tag.

Lecture

03

BEAUTIFULSOUP EXAMPLE

- Code:

```
import requests
from bs4 import BeautifulSoup
url = 'https://www.demoblaze.com/'
html = requests.get(url)
soup = BeautifulSoup(html.content, 'html.parser')
print(soup.prettify())
print(soup.title)
print(soup.title.string)
```

Lecture

03

BEAUTIFULSOUP EXAMPLE

Cont'd

- Code:

```
print( soup.find("p") )  
tags = soup('a')           #get all anchor tags as a ResultSet  
tags = soup.find_all("a")  #the same as above  
for tag in tags:  
    print( tag.get('href') )
```

Lecture

03

WEB SCRAPPING TO SEARCH FOR A JOB EXAMPLE

- Using Wuzzuf website:

```
from itertools import zip_longest
import requests
from bs4 import BeautifulSoup
import csv
```

```
result = requests.get('https://wuzzuf.net/search/jobs/?q=python&a=hpb')
soup = BeautifulSoup(result.content, 'html.parser')
job_titles = soup.find_all("h2", {"class":"css-m604qf"})
```

Lecture

03

WEB SCRAPPING TO SEARCH FOR A
JOB EXAMPLE

Cont'd

- Using Wuzzuf website:

```
company_names = soup.find_all("a", {"class":"css-17s97q8"})
locations = soup.find_all("span", {"class":"css-5wys0k"})
skills = soup.find_all("div", {"class":"css-y4udm8"})
print(len(job_titles))
jobs = []
comapnies = []
locs = []
skill = []
```

WEB SCRAPPING TO SEARCH FOR A JOB EXAMPLE

Cont'd

- Using Wuzzuf website:

```
for i in range(len(job_titles)):
    jobs.append(job_titles[i].text)
    comapnies.append(company_names[i].text)
    locs.append(locations[i].text)
    skill.append(skills[i].text)
```

WEB SCRAPPING TO SEARCH FOR A JOB EXAMPLE

Cont'd

- Using Wuzzuf website:

```
fileLists = [jobs, comapnies, locs, skill]
exported = zip_longest(*fileLists)
with open("/path/to/create/jobsResults.csv", "w") as f:
    wr = csv.writer(f)
    wr.writerow(["job title", "company name", "location", "skills"])
    wr.writerows(exported)
```

Lecture

03

SOCKETS

- **Sockets** are the endpoints of a bidirectional communications channel between connection devices.
- Sockets are the most popular form of inter-process communication especially for cross-platform communication.
- Sockets may communicate within a process, between processes on the same machine, or between processes on different continents.

Lecture

03

THE SOCKET MODULE

- Python's standard library consists of various built-in modules that support inter-process communication and networking.
- The **socket** module defines how server and client machines can communicate at hardware level using socket endpoints on top of the operating system.
- The socket module provides various objects, constants, functions and related exceptions for building full-fledged network applications including client and server programs.

Lecture

03

THE SOCKET MODULE

Cont'd

- To program a connection between two end-points, you need to configure both end-points sockets to know each other.
- The socket configuration includes:
 - Socket family: represents the IP version used.
 - **AF_INET** for IPv4
 - **AF_UNIX** for IPv6
 - Socket type: represents the type of connection.
 - **SOCK_STREAM** for connection-oriented type (TCP).
 - **SOCK_DGRAM** for connectionless type (UDP).

Lecture

03

THE SOCKET MODULE METHODS

- **socket()**: creates sockets objects for the server and the client.
- **gethostname()**: returns a string containing the hostname.
- **gethostbyname()**: returns IP address.
- **bind()**: binds/associates the address to the created socket object.

Lecture

03

THE SOCKET MODULE METHODS

Cont'd

- **connect():** takes a two-item tuple object as argument. The two items are IP address and port number of the server.
- **listen():** starts the server and runs it into a listen loop looking for connection request from client.
- **accept():** when a connection request is intercepted by server, this method accepts it and identifies the client socket with its address.
- **close():** marks the socket as closed.

Lecture

03

THE SOCKET CREATION

- Code:

```
import socket
```

```
# create a TCP socket
```

```
soc = socket.socket(socket.AF_INET, socket.SOCK_STREAM)
```

```
print("Socket succesfully created!")
```

Lecture

03

THE SOCKET CREATION WITH EXCEPTION HANDLING

- Code:

```
import socket
target_host = input("Enter the target host name to connect: ")
target_port = input("Enter the target port: ")
try:
    sock.connect((target_host, int(target_port)))
    print("Socket Connected to", target_host, "on port:", target_port)
except socket.error as err:
    print("Failed to connect to", target_host, "on port", target_port)
    print("Reason:", str(err) )
```

Lecture

03

SIMPLE SERVER USING SOCKETS

- Code:

```
import socket
```

```
soc = socket.socket()  
print("socket created")
```

```
# the server will be in the local machine  
soc.bind((socket.gethostname(), 5485))  
soc.listen(3) #accepts three connection  
print("Waiting for connections .....")
```

Lecture

03

QUESTIONS FOR ONLINE DISCUSSION

- Write a program and use this link <https://we-xpats.com/en/job/me/sa/search/?area=3411> to create a web scraping application to get the available jobs in Makkah.



Thank You

