

Final Project 2

PMG 497

Midocean University

Faculty of Management

Department/ Specialization



Techno-Economic Feasibility and Implementation
Roadmap for CO₂ Capture in [BHIG company]:
Comparative Assessment of Post-Combustion Solvent,
Adsorption, Membrane, and DAC Pathways

Abdullah Aljasim

.....

Final Project - 2

Faculty of Management - Midocean University

Supervisor

Dr.

Faculty member- Faculty of management- Midocean University

Date of submission – number of Semester

Abstract

Purpose:

Purpose: This study evaluates technical, economic, environmental, and regulatory feasibility of deploying CO₂ capture at [facility/region], comparing mature post-combustion amine systems with adsorption, membrane, oxy-fuel, and direct air capture (DAC) options, and delivering a phased development roadmap from concept to FEED and early operations with MRV integration.

Methodology:

The project synthesizes state-of-the-art technology reviews, screening-level process models, order-of-magnitude cost estimation, and comparative life-cycle assessment, aligned to a standard CCUS project funnel: feasibility, modeling, characterization, permitting, execution, and operations with MRV.

Findings:

For flue-gas CO₂ at 8–15% concentration, advanced post-combustion solvent systems remain most deployment-ready and cost-effective at scale; adsorption and membranes can be competitive in niche duty cycles or smaller modular units; oxy-fuel is site-specific; DAC remains strategic for removals but currently higher cost and energy-intensive. Policy signals and market growth (16% CAGR 2025–2034) and maturing supply chains improve bankability.

Originality & Implication:

Integrates 2025 innovations (modular hardware, improved sorbents, AI-enabled materials discovery, electro-swing approaches) with practical permitting and TRL-based stage-gates, translating global trends to a site-specific decision path.

Keywords:

Carbon capture; CCUS; post-combustion; adsorption; membranes; oxy-fuel; DAC; feasibility; TEA; LCA; MRV; permitting; TRL; storage; utilization

Table of Contents

Acknowledgment.....	Error! Bookmark not defined.
Dedication.....	Error! Bookmark not defined.
Abstract.....	2
1. Chapter 1: Introduction	5
1.1. Research Background.....	6
1.2. Research Problem.....	7
1.2.1. Theoretical Gaps	7
1.2.2. Practical Gaps	7
1.3. Research Significance	8
1.3.1. At the theoretical level	8
1.3.2. At the practical level	8
1.4. Research Questions	8
1.5. Research Objectives	9
1.6. Research Hypotheses.....	9
1.7. Research Model.....	9
1.8. Scope of The Study	10
1.9. The Project Structure.....	10
2. Chapter 2: Literature Review	11
2.1. Introduction	11
2.2. The independent variable	11
2.3. The dependent variable	12
2.4. The relationship between the independent and the dependent variables	12

2.5. Conclusion.....	12
3. Chapter 3: Research Methodology	12
3.1. Introduction	13
3.2. Operational definitions for research variables	13
3.3. Research design (research onion).....	14
3.4. Research population & Sampling methods and technique.....	14
3.5. Data collection method.....	15
3.6. Types of data	15
3.7. Statistical analysis procedures.....	15
3.8. Conclusion.....	16
4. Chapter 4: Statistical Analysis & Findings discussion.....	16
4.1. Introduction	17
4.2. Sample profile (descriptive statistics for research sample).....	17
4.3. Validity & reliability tests for the questionnaires	18
4.4. Descriptive statistics for research variables (answer research questions).....	18
4.5. Testing Hypotheses & Findings Discussion	18
4.6. Conclusion.....	19
5. Chapter five: Research limitations, Recommendations & Conclusion	20
5.1. Research Limitations & Future Research.....	20
5.2. Research Recommendations	20
References.....	21
Appendix.....	22

List of Figures:

List of Tables:

1. Chapter 1: Introduction

1.1. Research Background

Industrial decarbonization increasingly relies on CCUS to mitigate process and combustion emissions where electrification or fuel-switching are constrained by cost, technology readiness, or reliability needs in sectors like power, cement, steel, refining, hydrogen, and ammonia. Post-combustion capture has matured with next-gen solvents offering reduced energy penalties, while adsorption, membranes, and hybrid systems provide modularity and potential OPEX savings under specific conditions. DAC has emerged as a complementary pathway for durable carbon removals, yet near-term implementations must overcome current energy and cost hurdles pending scale and policy support.

1.2. Research Problem

1.2.1. [BHIG company] faces tightening emissions limits and net-zero commitments, requiring credible, costed pathways for CO₂ abatement that integrate with existing assets and local storage/utilization options. Decision-makers need a comparative, site-specific assessment of capture routes, balance-of-plant implications, storage vs. utilization logistics, and permitting/MRV to reduce risk before FEED.

Theoretical Gaps

There is a need to harmonize recent materials and process innovations with bankable project delivery frameworks that reflect TRL, regulatory constraints, and evolving incentive regimes to bridge lab-to-project transitions. Robust comparisons across varying flue compositions, load profiles, and integration constraints remain under-represented in generalized techno-economic studies.

1.2.2. Practical Gaps

Owners lack integrated views of capture technology fit, transport/storage readiness (geology, rights-of-way), MRV stack selection, and phased permitting aligned to execution risk and financing

milestones within regional policy contexts. Supply-chain scale-up and merchant CCUS models are advancing, but off-taker structures and credit monetization require clear project gating.

1.3. Research Significance

1.3.1. At the theoretical level

The study links capture-technology selection to a formal framework of technology readiness, energy penalty mechanisms, and verifiable carbon accounting, integrating multi-criteria decision analysis across solvents, adsorption, membranes, oxy-fuel, and DAC under consistent MRV definitions. This advances theory by connecting materials/process performance and system integration to quantifiable outcomes such as capture rate, levelized cost of capture, and permanence under recognized MRV typologies.

1.3.2. At the practical level

The study delivers a stage-gated roadmap from feasibility to pre-FEED/FEED that specifies data needs, site tie-ins, permitting pathways, transport/storage options, and MRV plans, enabling bankable CCUS decisions in real projects and jurisdictions. It operationalizes policy and market signals into implementation steps and risk controls relevant to regions like the GCC with strong storage potential and emerging CCUS hubs

1.4. Research Questions

- Which capture pathway best fits [BHIG company] considering flue gas specs, utilities, footprint, and integration constraints?
- What is the expected capture rate, energy penalty, and cost range at AACE Class 5–4 accuracy?
- What transport and storage/utilization options are viable regionally, and what are the key permitting and monitoring requirements?

- How do policy incentives and market trajectories affect project bankability and phasing?

1.5. Research Objectives

- Screen and compare solvent, adsorption, membrane, oxy-fuel, and DAC options for [BHIG company].
- Produce preliminary mass/energy balances, plot plans, and tie-ins for top options.
- Map transport (pipeline/truck/ship) and storage/utilization pathways with permitting/MRV.
- Deliver a stage-gated roadmap to pre-FEED and FEED with cost, schedule, and risks

1.6. Research Hypotheses

- H1: For [BHIG company] flue composition and duty, next-gen post-combustion solvent capture minimizes levelized capture cost vs. alternatives at $\geq 90\%$ capture.
- H2: Adsorption/membranes yield competitive NPV for smaller, modular, or intermittent sources when waste heat or low-carbon power is available.
- H3: DAC becomes viable if removal credits/offtakes are accessible and low-carbon energy is available at scale.

1.7. Research Model

The study applies a multi-criteria decision model integrating technical KPIs (capture rate, energy intensity, degradation), economic metrics (CapEx/Opex/LCOC), environmental outcomes (LCA, leakage risk), and regulatory fit (permitting, MRV, incentives) across project phases.

1.8. Scope of The Study

Covers capture unit integration at [facility], utility impacts, CO₂ conditioning and compression, transport corridor screening, storage/utilization readiness, permitting/MRV framing, and a pre-FEED readiness plan; excludes detailed FEED and construction execution plans.

1.9. The Project Structure

Chapter 2 reviews technology pathways;

Chapter 3 details methodology;

Chapter 4 presents screening results and discussion;

Chapter 5 provides recommendations, limitations, and future research.

2.Chapter 2: Literature Review

2.1. Introduction

Brief introduction for the chapter

2.2. The independent variable

2.3. The dependent variable

2.4. The relationship between the independent and the dependent variables

2.5. Conclusion

3. Chapter 3: Research Methodology

3.1. Introduction

3.2. Operational definitions for research variables

3.3. Research design (research onion)

3.4. Research population & Sampling methods and technique

3.5. Data collection method

3.6. Types of data

3.7. Statistical analysis procedures

3.8. Conclusion

4. Chapter 4: Statistical Analysis & Findings discussion

4.1. Introduction

4.2. Sample profile (descriptive statistics for research sample)

4.3. Validity & reliability tests for the questionnaires

4.4. Descriptive statistics for research variables (answer research questions)

4.5. Testing Hypotheses & Findings Discussion

4.6. Conclusion

5. Chapter five: Research limitations, Recommendations & Conclusion

5.1. Research Limitations & Future Research

5.2. Research Recommendations

5.3. Conclusion

References

Appendix