




جامعة الجميع الذكية
EVERYONE'S SMART UNIVERSITY



CCNA - Introduction to Networks v7.0 (ITN)
Prepared by Dr. Abdelrhman Ahmed
Lecture 5

Module 9: Address Resolution

What to Expect in this Module

- To facilitate learning, the following features within the GUI may be included in this module:

Feature	Description
Animations	Expose learners to new skills and concepts.
Videos	Expose learners to new skills and concepts.
Check Your Understanding(CYU)	Per topic online quiz to help learners gauge content understanding.
Interactive Activities	A variety of formats to help learners gauge content understanding.
Syntax Checker	Small simulations that expose learners to Cisco command line to practice configuration skills.
PT Activity	Simulation and modeling activities designed to explore, acquire, reinforce, and expand skills.

Module Objectives

Module Title: Address Resolution

Module Objective: Explain how ARP and ND enable communication on a network.

Topic Title	Topic Objective
MAC and IP	Compare the roles of the MAC address and the IP address.
ARP	Describe the purpose of ARP.
Neighbor Discovery	Describe the operation of IPv6 neighbor discovery.

MAC and IP

Destination on Same Network

There are two primary addresses assigned to a device on an Ethernet LAN:

- **Layer 2 physical address (the MAC address)** – Used for NIC to NIC communications on the same Ethernet network.
- **Layer 3 logical address (the IP address)** – Used to send the packet from the source device to the destination device.

Layer 2 addresses are used to deliver frames from one NIC to another NIC on the same network. If a destination IP address is on the same network, the destination MAC address will be that of the destination device.




Destination MAC	Source MAC	Source IPv4	Destination IPv4
55-55-55	aa-aa-aa	192.168.10.10	192.168.10.11

MAC and IP

Destination on Remote Network

When the destination IP address is on a remote network, the destination MAC address is that of the default gateway.

- ARP is used by IPv4 to associate the IPv4 address of a device with the MAC address of the device NIC.
- ICMPv6 is used by IPv6 to associate the IPv6 address of a device with the MAC address of the device NIC.




Destination MAC	Source MAC	Source IPv4	Destination IPv4
bb-bb-bb	aa-aa-aa	192.168.10.10	10.1.1.10

ARP Overview

A device uses ARP to determine the destination MAC address of a local device when it knows its IPv4 address.

ARP provides two basic functions:

- Resolving IPv4 addresses to MAC addresses
- Maintaining an ARP table of IPv4 to MAC address mappings




ARP ARP Functions

To send a frame, a device will search its ARP table for a destination IPv4 address and a corresponding MAC address.

- If the packet's destination IPv4 address is on the same network, the device will search the ARP table for the destination IPv4 address.
- If the destination IPv4 address is on a different network, the device will search the ARP table for the IPv4 address of the default gateway.
- If the device locates the IPv4 address, its corresponding MAC address is used as the destination MAC address in the frame.
- If there is no ARP table entry is found, then the device sends an ARP request.

Removing Entries from an ARP Table

- Entries in the ARP table are not permanent and are removed when an ARP cache timer expires after a specified period of time.
- The duration of the ARP cache timer differs depending on the operating system.
- ARP table entries can also be removed manually by the administrator.



ARP ARP Tables on Networking Devices

- The **show ip arp** command displays the ARP table on a Cisco router.
- The **arp -a** command displays the ARP table on a Windows 10 PC.

```
R1# show ip arp
Protocol  Address          Age (min)  Hardware Addr  Type   Interface
Internet  192.168.10.1      -          a0e0.af0d.e140  ARPA   GigabitEthernet0/0/0
```


```
C:\Users\PC> arp -a
```

```
Interface: 192.168.1.124 --- 0x10
Internet Address      Physical Address      Type
192.168.1.1           c8-d7-19-cc-a0-86     dynamic
192.168.1.101         08-3e-0c-f5-f7-77     dynamic
```

ARP

ARP Issues – ARP Broadcasting and ARP Spoofing

- ARP requests are received and processed by every device on the local network.
- Excessive ARP broadcasts can cause some reduction in performance.
- ARP replies can be spoofed by a threat actor to perform an ARP poisoning attack.
- Enterprise level switches include mitigation techniques to protect against ARP attacks.



IPv6 Neighbor Discovery


IPv6 Neighbor Discovery Messages

IPv6 Neighbor Discovery (ND) protocol provides:

- Address resolution
- Router discovery
- Redirection services
- ICMPv6 Neighbor Solicitation (NS) and Neighbor Advertisement (NA) messages are used for device-to-device messaging such as address resolution.
- ICMPv6 Router Solicitation (RS) and Router Advertisement (RA) messages are used for messaging between devices and routers for router discovery.
- ICMPv6 redirect messages are used by routers for better next-hop selection.

IPv6 Neighbor Discovery

IPv6 Neighbor Discovery – Address Resolution




- IPv6 devices use ND to resolve the MAC address of a known IPv6 address.
- ICMPv6 Neighbor Solicitation messages are sent using special Ethernet and IPv6 multicast addresses.

The End

Please feel free to contact me anytime if you have any questions

Abdelrhman Ahmed Refaat:
abdelrhmanahmedrefaat@gmail.com



جامعة القادسية
EVERYONE'S SMART UNIVERSITY