

Natural Language Processing (AI615)

Prepared by Dr. Ashraf Elsayed

Lecture 10



Neural Language Models & Part of Speech Tagging

Lecture 10


Prepared by
Dr. Ashraf Elsayed

The objectives of this lecture is to:

- Understand Neural Language Models
- Define and understand Feedforward Neural Networks
- Understand Parts of Speech (POS)
- Define and Explain Named Entity Recognition (NER)

Neural Language Models

This is in your brain



By BruceBlaus - Own work, CC BY 3.0,
<https://commons.wikimedia.org/w/index.php?curid=28761830>

Neural Network Unit

This is not in your brain


Output value

Non-linear transform

Weighted sum

Weights

Input layer



Neural unit

- Take weighted sum of inputs, plus a bias

$$z = b + \sum_i w_i x_i$$

$$z = w \cdot x + b$$

- Instead of just using z , we'll apply a nonlinear activation function f :


$$y = a = f(z)$$

Non-Linear Activation Functions

We've already seen the sigmoid for logistic regression:

Sigmoid

$$y = s(z) = \frac{1}{1 + e^{-z}}$$



Final function the unit is computing

$$y = s(w \cdot x + b) = \frac{1}{1 + \exp(-(w \cdot x + b))}$$

Final unit again


Output value

Non-linear activation function

Weighted sum

Weights

Input layer



An example

- *Suppose a unit has:*
- $w = [0.2, 0.3, 0.9]$
- $b = 0.5$
- What happens with input x :
- $x = [0.5, 0.6, 0.1]$

$$y = s(w \cdot x + b) =$$

An example

- *Suppose a unit has:*

- $w = [0.2, 0.3, 0.9]$

- $b = 0.5$

- What happens with the following input x ?

- $x = [0.5, 0.6, 0.1]$

$$y = s(w \cdot x + b) = \frac{1}{1 + e^{-(w \cdot x + b)}} =$$

An example

- *Suppose a unit has:*
 - $w = [0.2, 0.3, 0.9]$
 - $b = 0.5$
- What happens with input x :
 - $x = [0.5, 0.6, 0.1]$

$$y = s(w \cdot x + b) = \frac{1}{1 + e^{-(w \cdot x + b)}} = \frac{1}{1 + e^{-(.5 \cdot .2 + .6 \cdot .3 + .1 \cdot .9 + .5)}} =$$

An example


- Suppose a unit has:
 - $w = [0.2, 0.3, 0.9]$
 - $b = 0.5$
- What happens with input x :
- $x = [0.5, 0.6, 0.1]$

$$y = s(w \cdot x + b) = \frac{1}{1 + e^{-(w \cdot x + b)}} =$$


$$\frac{1}{1 + e^{-(.5 \cdot .2 + .6 \cdot .3 + .1 \cdot .9 + .5)}} = \frac{1}{1 + e^{-0.87}} = .70$$

Non-Linear Activation Functions besides sigmoid

Most Common:



tanh




ReLU

Rectified Linear Unit

Feedforward Neural Networks

- Can also be called **multi-layer perceptrons** (or **MLPs**) for historical reasons



Binary Logistic Regression as a 1-layer Network

(we don't count the input layer in counting layers!)

Output layer
(σ node)

$$y = \sigma(w \cdot x + b)$$

(y is a scalar)


w
(vector)

w_1

w_n

b (scalar)

Input layer
vector x



Multinomial Logistic Regression as a 1-layer Network

Fully connected single layer network

Output layer
(softmax nodes)

$$y = \text{softmax}(Wx + b)$$


y is a vector

W is a
matrix

b

b is a vector

Input layer
scalars



Reminder: softmax: a generalization of sigmoid

- For a vector z of dimensionality k , the softmax is:

$$\text{softmax}(z) = \left[\frac{\exp(z_1)}{\sum_{i=1}^k \exp(z_i)}, \frac{\exp(z_2)}{\sum_{i=1}^k \exp(z_i)}, \dots, \frac{\exp(z_k)}{\sum_{i=1}^k \exp(z_i)} \right]$$

- Example:

$$\text{softmax}(z_i) = \frac{\exp(z_i)}{\sum_{j=1}^k \exp(z_j)} \quad 1 \leq i \leq k$$

$$z = [0.6, 1.1, -1.5, 1.2, 3.2, -1.1]$$

$$\text{softmax}(z) = [0.055, 0.090, 0.006, 0.099, 0.74, 0.010]$$

Two-Layer Network with scalar output

Output layer
(σ node)


$$y = \sigma(z) \quad y \text{ is a scalar}$$
$$z = Uh$$

hidden units
(σ node)

$$h = \sigma(Wx + b)$$

Could be ReLU
Or tanh

Input layer
(vector)



Two-Layer Network with scalar output

Output layer
(σ node)


$$y = \sigma(z) \quad y \text{ is a scalar}$$

$$z = Uh$$

hidden units
(σ node)

$$h = \sigma(Wx + b)$$

Input layer
(vector)



Two-Layer Network with scalar output

Output layer
(σ node)


$$y = \sigma(z) \quad y \text{ is a scalar}$$
$$z = Uh$$

hidden units
(σ node)

$$h = \sigma(Wx + b)$$

Could be ReLU
Or tanh

Input layer
(vector)




Two-Layer Network with softmax output

Output layer
(σ node)

hidden units
(σ node)

Input layer
(vector)



$$y = \text{softmax}(z)$$

$$z = Uh$$

y is a vector

$$h = \sigma(Wx + b)$$

Could be ReLU
Or tanh

Multi-layer Notation


$$y = a^{[2]}$$

$$a^{[2]} = g^{[2]}(z^{[2]}) \quad \text{sigmoid or softmax}$$

$$z^{[2]} = W^{[2]}a^{[1]} + b^{[2]}$$

$$a^{[1]} = g^{[1]}(z^{[1]}) \quad \text{ReLU}$$

$$z^{[1]} = W^{[1]}a^{[0]} + b^{[1]}$$



Multi Layer Notation


$$z^{[1]} = W^{[1]}a^{[0]} + b^{[1]}$$

$$a^{[1]} = g^{[1]}(z^{[1]})$$

$$z^{[2]} = W^{[2]}a^{[1]} + b^{[2]}$$

$$a^{[2]} = g^{[2]}(z^{[2]})$$

$$\hat{y} = a^{[2]}$$



for i in 1..n

$$z^{[i]} = W^{[i]} a^{[i-1]} + b^{[i]}$$

$$a^{[i]} = g^{[i]}(z^{[i]})$$

$$\hat{y} = a^{[n]}$$

Replacing the bias unit

- Let's switch to a notation without the bias unit
- Just a notational change
 1. Add a dummy node $a_0=1$ to each layer
 2. Its weight w_0 will be the bias
 3. So input layer $a^{[0]}_0=1$,
 - And $a^{[1]}_0=1$, $a^{[2]}_0=1,...$

Replacing the bias unit

• Instead of:

$$x = x_1, x_2, \dots, x_{n_0}$$

$$h = \sigma(Wx + b)$$

$$h_j = \sigma \left(\sum_{i=1}^{n_0} W_{ji} x_i + b_j \right)$$

We'll do this:


$$x = x_0, x_1, x_2, \dots, x_{n_0}$$

$$h = \sigma(Wx)$$


$$\sigma \left(\sum_{i=0}^{n_0} W_{ji} x_i \right)$$

Replacing the bias unit

Instead of:



We'll do this:




Use cases for feedforward networks

- Let's consider 2 (simplified) sample tasks:
 1. Text classification
 2. Language modeling
- State of the art systems use more powerful neural architectures, but simple models are useful to consider!

Classification: Sentiment Analysis

- We could do exactly what we did with logistic regression
- Input layer are binary features as before
- Output layer is 0 or 1




Sentiment Features


Var	Definition
x_1	$\text{count}(\text{positive lexicon}) \in \text{doc}$
x_2	$\text{count}(\text{negative lexicon}) \in \text{doc}$
x_3	$\begin{cases} 1 & \text{if "no"} \in \text{doc} \\ 0 & \text{otherwise} \end{cases}$
x_4	$\text{count}(\text{1st and 2nd pronouns}) \in \text{doc}$
x_5	$\begin{cases} 1 & \text{if "!"} \in \text{doc} \\ 0 & \text{otherwise} \end{cases}$
x_6	$\log(\text{word count of doc})$

Feedforward nets for simple classification

Logistic
Regression




2-layer
feedforward
network




- Just adding a hidden layer to logistic regression
- allows the network to use non-linear interactions between features
- which may (or may not) improve performance.

Even better: representation learning

- The real power of deep learning comes from the ability to **learn** features from the data
- Instead of using hand-built human-engineered features for classification
- Use learned representations like embeddings!




Neural Net Classification with embeddings as input features!



Issue: texts come in different sizes

- This assumes a fixed size length (3)!
- Kind of unrealistic.
- Some simple solutions (more sophisticated solutions later)




1. Make the input the length of the longest review
 - If shorter then pad with zero embeddings
 - Truncate if you get longer reviews at test time
2. Create a single "sentence embedding" (the same dimensionality as a word) to represent all the words
 - Take the mean of all the word embeddings
 - Take the element-wise max of all the word embeddings
 - For each dimension, pick the max value from all words

Reminder: Multiclass Outputs

- What if you have more than two output classes?
 - Add more output units (one for each class)
 - And use a “softmax layer”

$$\text{softmax}(z_i) = \frac{e^{z_i}}{\sum_{j=1}^k e^{z_j}} \quad 1 \leq i \leq D$$



Neural Language Models (LMs)


- **Language Modeling:** Calculating the probability of the next word in a sequence given some history.
- We've seen N-gram based LMs
- But neural network LMs far outperform n-gram language models
- State-of-the-art neural LMs are based on more powerful neural network technology like Transformers
- But **simple feedforward LMs** can do almost as well!

Simple feedforward Neural Language Models

- **Task:** predict next word w_t
- given prior words $w_{t-1}, w_{t-2}, w_{t-3}, \dots$
- **Problem:** Now we're dealing with sequences of arbitrary length.
- **Solution:** Sliding windows (of fixed length)

$$P(w_t | w_1^{t-1}) \approx P(w_t | w_{t-N+1}^{t-1})$$

Neural Language Model




Why Neural LMs work better than N-gram LMs

- **Training data:**
 - We've seen: I have to make sure that the cat gets fed.
 - Never seen: dog gets fed
- **Test data:**
 - I forgot to make sure that the dog gets ____
 - N-gram LM can't predict "fed"!
 - Neural LM can use similarity of "cat" and "dog" embeddings to generalize and predict "fed" after dog

Training Neural Nets: Overview

Intuition: training a 2-layer Network



Intuition: Training a 2-layer network

- For every training tuple (x, y)
 - Run *forward* computation to find our estimate $\hat{y}$
 - Run *backward* computation to update weights:
 - For every output node
 - Compute loss L between true y and the estimated $\hat{y}$
 - For every weight w from hidden layer to the output layer
 - Update the weight
 - For every hidden node
 - Assess how much blame it deserves for the current answer
 - For every weight w from input layer to the hidden layer
 - Update the weight

Reminder: Loss Function for binary logistic regression

- A measure for how far off the current answer is to the right answer
- Cross entropy loss for logistic regression:

$$\begin{aligned} L_{\text{CE}}(\hat{y}, y) &= -\log p(y|x) = -[y \log \hat{y} + (1 - y) \log(1 - \hat{y})] \\ &= -[y \log \sigma(w \cdot x + b) + (1 - y) \log(1 - \sigma(w \cdot x + b))] \end{aligned}$$

Reminder: gradient descent for weight updates

- Use the derivative of the loss function with respect to weights

$$\frac{d}{dw} L(f(x; w), y)$$

- To tell us how to adjust weights for each training item

- Move them in the opposite direction of the gradient


- For logistic regression

$$w^{t+1} = w^t - h \frac{d}{dw} L(f(x; w), y)$$

$$\frac{\partial L_{CE}(\hat{y}, y)}{\partial w_j} = [\sigma(w \cdot x + b) - y] x_j$$

Where did that derivative come from?

- Using the chain rule! $f(x) = u(v(x))$
$$\frac{df}{dx} = \frac{du}{dv} \cdot \frac{dv}{dx}$$



Derivative of the weighted sum

Derivative of the Activation

Derivative of the Loss

$$\frac{\partial L}{\partial w_i} = \frac{\partial L}{\partial y} \frac{\partial y}{\partial z} \frac{\partial z}{\partial w_i}$$

How can I find that gradient for every weight in the network?

- These derivatives on the prior slide only give the updates for one weight layer: the last one!
- What about deeper networks?
- Lots of layers, different activation functions?
- Solution:
- Even more use of the chain rule!!
- Computation graphs and backward differentiation!

Computation Graphs and Backward Differentiation

Why Computation Graphs

- For training, we need the derivative of the loss with respect to each weight in every layer of the network
- But the loss is computed only at the very end of the network!
- Solution: **error backpropagation** (Rumelhart, Hinton, Williams, 1986)
- **Backprop** is a special case of **backward differentiation**
- Which relies on **computation graphs**.

Computation Graphs

A computation graph represents the process of computing a mathematical expression

Example:


$$L(a, b, c) = c(a + 2b)$$

$$d = 2 * b$$

$$e = a + d$$

$$L = c * e$$

Computations:



Example:


$$L(a, b, c) = c(a + 2b)$$

$$d = 2 * b$$

Computations:

$$e = a + d$$

$$L = c * e$$



Backwards differentiation in computation graphs

- The importance of the computation graph comes from the backward pass
- This is used to compute the derivatives that we'll need for the weight update.

Example

$$L(a, b, c) = c(a + 2b)$$

$$d = 2 * b$$

$$e = a + d$$

$$L = c * e$$

We want: $\frac{\partial L}{\partial a}$, $\frac{\partial L}{\partial b}$, and $\frac{\partial L}{\partial c}$

The derivative $\frac{\partial L}{\partial a}$, tells us how much a small change in a affects L .

The chain rule

- Computing the derivative of a composite function:

- $f(x) = u(v(x))$

$$\frac{df}{dx} = \frac{du}{dv} \cdot \frac{dv}{dx}$$

- $f(x) = u(v(w(x)))$

-

$$\frac{df}{dx} = \frac{du}{dv} \cdot \frac{dv}{dw} \cdot \frac{dw}{dx}$$

Example

$$L(a, b, c) = c(a + 2b)$$

$$d = 2 * b$$

$$e = a + d$$

$$L = c * e$$

$$\frac{\partial L}{\partial c} = e$$

$$\frac{\partial L}{\partial a} = \frac{\partial L}{\partial e} \frac{\partial e}{\partial a}$$

$$\frac{\partial L}{\partial b} = \frac{\partial L}{\partial e} \frac{\partial e}{\partial d} \frac{\partial d}{\partial b}$$

Example

$$L(a, b, c) = c(a + 2b)$$

$$d = 2 * b$$

$$e = a + d$$

$$L = c * e$$

$$\frac{\partial L}{\partial a} = \frac{\partial L}{\partial e} \frac{\partial e}{\partial a}$$

$$\frac{\partial L}{\partial b} = \frac{\partial L}{\partial e} \frac{\partial e}{\partial d} \frac{\partial d}{\partial b}$$

$$L = ce : \quad \frac{\partial L}{\partial e} = c, \frac{\partial L}{\partial c} = e$$

$$e = a + d : \quad \frac{\partial e}{\partial a} = 1, \frac{\partial e}{\partial d} = 1$$

$$d = 2b : \quad \frac{\partial d}{\partial b} = 2$$


$$\frac{\partial L}{\partial a} = \frac{\partial L}{\partial e} \frac{\partial e}{\partial a}$$

$$\frac{\partial L}{\partial b} = \frac{\partial L}{\partial e} \frac{\partial e}{\partial d} \frac{\partial d}{\partial b}$$


$$L = ce : \quad \frac{\partial L}{\partial e} = c, \quad \frac{\partial L}{\partial c} = e$$

$$e = a + d : \quad \frac{\partial e}{\partial a} = 1, \quad \frac{\partial e}{\partial d} = 1$$


$$d = 2b : \quad \frac{\partial d}{\partial b} = 2$$



Example



Backward differentiation on a two layer network



$$z^{[1]} = W^{[1]} \mathbf{x} + b^{[1]}$$

$$a^{[1]} = \text{ReLU}(z^{[1]})$$

$$z^{[2]} = W^{[2]} a^{[1]} + b^{[2]}$$

$$a^{[2]} = \sigma(z^{[2]})$$

$$\hat{y} = a^{[2]}$$

Backward differentiation on a two layer network

$$z^{[1]} = W^{[1]} \mathbf{x} + b^{[1]}$$

$$a^{[1]} = \text{ReLU}(z^{[1]})$$

$$z^{[2]} = W^{[2]} a^{[1]} + b^{[2]}$$


$$a^{[2]} = \sigma(z^{[2]})$$

$$\hat{y} = a^{[2]}$$

$$\frac{d \text{ReLU}(z)}{dz} = \begin{cases} 0 & \text{for } z < 0 \\ 1 & \text{for } z \geq 0 \end{cases}$$

$$\frac{d\sigma(z)}{dz} = \sigma(z)(1 - \sigma(z))$$

Backward differentiation on a 2-layer network



Starting off the backward pass: $\frac{\partial L}{\partial z}$

(I'll write a for $a^{[2]}$ and z for $z^{[2]}$)

$$L(\hat{y}, y) = -(y \log(\hat{y}) + (1 - y) \log(1 - \hat{y}))$$

$$L(a, y) = -(y \log a + (1 - y) \log(1 - a))$$

$$\frac{\partial L}{\partial z} = \frac{\partial L}{\partial a} \frac{\partial a}{\partial z}$$

$$\begin{aligned} \frac{\partial L}{\partial a} &= - \left(\left(y \frac{\partial \log(a)}{\partial a} \right) + (1 - y) \frac{\partial \log(1 - a)}{\partial a} \right) \\ &= - \left(\left(y \frac{1}{a} \right) + (1 - y) \frac{1}{1 - a} (-1) \right) = - \left(\frac{y}{a} + \frac{y - 1}{1 - a} \right) \end{aligned}$$

$$\frac{\partial a}{\partial z} = a(1 - a)$$

$$\frac{\partial L}{\partial z} = - \left(\frac{y}{a} + \frac{y - 1}{1 - a} \right) a(1 - a) = a - y$$

$$z^{[1]} = W^{[1]} \mathbf{x} + b^{[1]}$$

$$a^{[1]} = \text{ReLU}(z^{[1]})$$

$$z^{[2]} = W^{[2]} a^{[1]} + b^{[2]}$$

$$a^{[2]} = \sigma(z^{[2]})$$

$$\hat{y} = a^{[2]}$$

Summary

- For training, we need the derivative of the loss with respect to weights in early layers of the network
- But loss is computed only at the very end of the network!
- Solution: **backward differentiation**
- Given a computation graph and the derivatives of all the functions in it we can automatically compute the derivative of the loss with respect to these early weights.

Parts of Speech

- From the earliest linguistic traditions (Yaska and Panini 5th C. BCE, Aristotle 4th C. BCE), the idea that words can be classified into grammatical categories
 - Part of speech, word classes, POS, POS tags
- 8 parts of speech attributed to Dionysius Thrax of Alexandria (c. 1st C. BCE):
 - noun, verb, pronoun, preposition, adverb, conjunction, participle, article
 - These categories are relevant for NLP today.

Two classes of words: Open vs. Closed

- Closed class words
 - Relatively fixed membership
 - Usually **function** words: short, frequent words with grammatical function
 - determiners: *a, an, the*
 - pronouns: *she, he, I*
 - prepositions: *on, under, over, near, by, ...*
- Open class words
 - Usually **content** words: Nouns, Verbs, Adjectives, Adverbs
 - Plus interjections: *oh, ouch, uh-huh, yes, hello*
 - New nouns and verbs like *iPhone* or *to fax*

Open class ("content") words

Nouns

Proper

Janet
Italy

Common

cat, cats
mango

Verbs

Main

eat
went

Adjectives

old green tasty

Adverbs

slowly yesterday

Numbers

122,312
one

Interjections

Ow hello
... more

Closed class ("function")

Determiners

the some

Conjunctions

and or

Pronouns

they its

Auxiliary

can
had

Prepositions

to with

Particles

off up


... more

Part-of-Speech Tagging

- Assigning a part-of-speech to each word in a text.
- Words often have more than one POS.
- **book:**
 - VERB: (***Book** that flight*)
 - NOUN: (*Hand me that **book***).

Part-of-Speech Tagging

Map from sequence $x_1, \dots, x_n$ of words to $y_1, \dots, y_n$ of POS tags



"Universal Dependencies" Tagset

	Tag	Description	Example
Open Class	ADJ	Adjective: noun modifiers describing properties	<i>red, young, awesome</i>
	ADV	Adverb: verb modifiers of time, place, manner	<i>very, slowly, home, yesterday</i>
	NOUN	words for persons, places, things, etc.	<i>algorithm, cat, mango, beauty</i>
	VERB	words for actions and processes	<i>draw, provide, go</i>
	PROPN	Proper noun: name of a person, organization, place, etc..	<i>Regina, IBM, Colorado</i>
	INTJ	Interjection: exclamation, greeting, yes/no response, etc.	<i>oh, um, yes, hello</i>
Closed Class Words	ADP	Adposition (Preposition/Postposition): marks a noun's spacial, temporal, or other relation	<i>in, on, by under</i>
	AUX	Auxiliary: helping verb marking tense, aspect, mood, etc.,	<i>can, may, should, are</i>
	CCONJ	Coordinating Conjunction: joins two phrases/clauses	<i>and, or, but</i>
	DET	Determiner: marks noun phrase properties	<i>a, an, the, this</i>
	NUM	Numeral	<i>one, two, first, second</i>
	PART	Particle: a preposition-like form used together with a verb	<i>up, down, on, off, in, out, at, by</i>
	PRON	Pronoun: a shorthand for referring to an entity or event	<i>she, who, I, others</i>
	SCONJ	Subordinating Conjunction: joins a main clause with a subordinate clause such as a sentential complement	<i>that, which</i>
Other	PUNCT	Punctuation	<i>; , ()</i>
	SYM	Symbols like \$ or emoji	<i>\$, %</i>
	X	Other	<i>asdf, qwfg</i>

Sample "Tagged" English sentences

- There/**PRO** were/**VERB** 70/**NUM** children/**NOUN** there/**ADV** ./**PUNC**
- Preliminary/**ADJ** findings/**NOUN** were/**AUX** reported/**VERB** in/**ADP** today/**NOUN** 's/**PART** New/**PROPN** England/**PROPN** Journal/**PROPN** of/**ADP** Medicine/**PROPN**

Why Part of Speech Tagging?

- Can be useful for other NLP tasks
 - Parsing: POS tagging can improve syntactic parsing
 - MT: reordering of adjectives and nouns (say from Spanish to English)
 - Sentiment or affective tasks: may want to distinguish adjectives or other POS
 - Text-to-speech (how do we pronounce “lead” or “object”?)

How difficult is POS tagging in English?

- Roughly 15% of word types are ambiguous
 - Hence 85% of word types are unambiguous
 - Janet is always PROP, hesitantly is always ADV
- But those 15% tend to be very common.
- So ~60% of word tokens are ambiguous
 - E.g., *back*
 - earnings growth took a *back*/ADJ seat
 - a small building in the *back*/NOUN
 - a clear majority of senators *back*/VERB the bill
 - enable the country to buy *back*/PART debt
 - I was twenty-one *back*/ADV then

POS tagging performance in English

- How many tags are correct? (Tag accuracy)
 - About 97%
 - Hasn't changed in the last 10+ years
 - HMMs, CRFs, BERT perform similarly .
 - Human accuracy about the same
- But baseline is 92%!
 - Baseline is performance of stupidest possible method
 - "Most frequent class baseline" is an important baseline for many tasks
 - Tag every word with its most frequent tag
 - (and tag unknown words as nouns)
 - Partly easy because
 - Many words are unambiguous

Sources of information for POS tagging

Janet **will** back the **bill**
AUX/NOUN/VERB? **NOUN/VERB?**

- Prior probabilities of word/tag
 - "**will**" is usually an AUX
- Identity of neighboring words
 - "**the**" means the next word is probably not a verb
- Morphology and wordshape:
 - Prefixes **unable:** **un-** →
ADJ
 - Suffixes **importantly:** **-ly** → ADJ
 - Capitalization **Janet:** **CAP** → PROP

Standard algorithms for POS tagging

- Supervised Machine Learning Algorithms:
 - Hidden Markov Models
 - Conditional Random Fields (CRF)/ Maximum Entropy Markov Models (MEMM)
 - Neural sequence models (RNNs or Transformers)
 - Large Language Models (like BERT), finetuned
- All required a hand-labeled training set, all about equal performance (97% on English)
- All make use of information sources we discussed
 - Via human created features: HMMs and CRFs
 - Via representation learning: Neural LMs

Named Entities

- **Named entity**, in its core usage, means anything that can be referred to with a proper name. Most common 4 tags:
 - **PER** (Person): “Marie Curie”
 - **LOC** (Location): “New York City”
 - **ORG** (Organization): “Stanford University”
 - **GPE** (Geo-Political Entity): “Boulder, Colorado”
- Often multi-word phrases
- But the term is also extended to things that aren't entities:
 - dates, times, prices

Named Entity tagging

- The task of named entity recognition (NER):
 - find spans of text that constitute proper names
 - tag the type of the entity.

NER output

Citing high fuel prices, [ORG United Airlines] said [TIME Friday] it has increased fares by [MONEY \$6] per round trip on flights to some cities also served by lower-cost carriers. [ORG American Airlines], a unit of [ORG AMR Corp.], immediately matched the move, spokesman [PER Tim Wagner] said. [ORG United], a unit of [ORG UAL Corp.], said the increase took effect [TIME Thursday] and applies to most routes where it competes against discount carriers, such as [LOC Chicago] to [LOC Dallas] and [LOC Denver] to [LOC San Francisco].

Why NER?

- Sentiment analysis: consumer's sentiment toward a particular company or person?
- Question Answering: answer questions about an entity?
- Information Extraction: Extracting facts about entities from text.

Why NER is hard

1) Segmentation

- In POS tagging, no segmentation problem since each word gets one tag.
- In NER we have to find and segment the entities!

2) Type ambiguity

[PER Washington] was born into slavery on the farm of James Burroughs.
[ORG Washington] went up 2 games to 1 in the four-game series.
Blair arrived in [LOC Washington] for what may well be his last state visit.
In June, [GPE Washington] passed a primary seatbelt law.

BIO Tagging

- How can we turn this structured problem into a sequence problem like POS tagging, with one label per word?
- [PER Jane Villanueva] of [ORG United] , a unit of [ORG United Airlines Holding] , said the fare applies to the [LOC Chicago] route.

BIO Tagging

- [PER Jane Villanueva] of [ORG United] , a unit of [ORG United Airlines Holding] , said the fare applies to the [LOC Chicago] route.

Words	BIO Label
Jane	B-PER
Villanueva	I-PER
of	O
United	B-ORG
Airlines	I-ORG
Holding	I-ORG
discussed	O
the	O
Chicago	B-LOC
route	O
.	O

Now we have one tag per token!!!

BIO Tagging

- B: token that *begins* a span
- I: tokens *inside* a span
- O: tokens outside of any span

Words	BIO Label
Jane	B-PER
Villanueva	I-PER
of	O
United	B-ORG
Airlines	I-ORG
Holding	I-ORG
discussed	O
the	O
Chicago	B-LOC
route	O
.	O

Standard algorithms for NER

- Supervised Machine Learning given a human-labeled training set of text annotated with tags
- Hidden Markov Models
- Conditional Random Fields (CRF)/ Maximum Entropy Markov Models (MEMM)
- Neural sequence models (RNNs or Transformers)
- Large Language Models (like BERT), finetuned

Summary

- Understand Neural Language Models
- Define and understand Feedforward Neural Networks
- Understand Parts of Speech (POS)
- Define and Explain Named Entity Recognition (NER)



Thank You