

Literature Review

1

Recognizing American Sign Language gestures efficiently and accurately using a hybrid transformer model

The authors proposed a hybrid model that included a dual-path Convolutional Neural Network (CNN) architecture integrated with a Vision Transformer (ViT) module to recognize 29 different signs from American Sign Language (ASL) images. They applied this hybrid approach to extract both global gesture features and localized hand-specific details, which were then merged using element-wise multiplication to enhance the recognition of subtle movements. The researchers utilized the ASL Alphabet Dataset for training and testing, which consisted of approximately 87,000 RGB images featuring a wide variety of hand poses and lighting conditions. The results showed that their proposed hybrid model achieved the best accuracy at 99.97% over 29 different signs and maintained a high processing speed of 110 FPS compared to other standalone models.

The results showed that their proposed model achieved the best accuracy at 99.97 over 29 different signs.

2

Sign Language Recognition for Arabic Alphabets Using Transfer Learning Technique

The authors proposed a vision-based recognition system that utilized Transfer Learning techniques to recognize 32 different signs from the Arabic Sign Language (ArSL) alphabet. They applied several pre-trained Deep Learning models, specifically focusing on EfficientNetB4, to extract complex features from hand gestures and handle variations in signing styles. The researchers utilized the ArSL2018 dataset for training and testing, which consisted of 54,049 RGB images collected from 40 different subjects to ensure diversity in lighting and hand positions.

The results showed that their proposed model achieved the best accuracy at 95% over 32 different signs and demonstrated superior performance in handling complex image backgrounds compared to other standalone models.

3

Real-Time Sign Language Fingerspelling Recognition System Using 2D Deep CNN with Two-Stream Feature Extraction Approach

The authors proposed a real-time fingerspelling recognition system that utilized a 2D Deep Convolutional Neural Network (CNN) with a two-stream feature extraction approach. They applied this method to capture both spatial and temporal information from dynamic hand gestures to improve communication for the deaf community. The researchers utilized a comprehensive dataset for training and validation, which consisted of a diverse range of gestures recorded across different environmental settings.

The results showed that their proposed model significantly outperformed traditional machine learning techniques and achieved high recognition accuracy even with increased data volume.

4

Sign Language to Text and Speech Conversion

The authors proposed a real-time system to convert American Sign Language (ASL) fingerspelling into both text and speech using a Convolutional Neural Network (CNN). They applied a specialized filter to the hand images before passing them to the classifier to enhance the prediction of gesture classes. The researchers utilized a dataset of ASL hand gestures for training and testing to ensure the model could recognize various letters accurately.

The results showed that their proposed model attained high accuracy in predicting gestures and provided an effective way for hearing-impaired individuals to communicate with others in real-time.

5

Semantic Communications for Image-Based Sign Language Transmission

The authors proposed a novel system for image-based semantic communications specifically designed for American Sign Language (ASL) transmission. They applied a specialized encoder-decoder architecture that transformed ASL images into semantic feature vectors to reduce data size while preserving meaning. The researchers utilized the ASL Alphabet Dataset to validate the system's ability to reconstruct original images even under noisy wireless channel conditions.

The results showed that their proposed semantic approach outperformed traditional communication methods by maintaining high structural similarity and recognition accuracy at much lower transmission rates.

6

Vision-based sign language recognition system: A Comprehensive Review

The author provided a comprehensive review of vision-based sign language recognition systems to highlight existing techniques and their comparisons. They analyzed various image processing stages, including preprocessing, feature extraction, and classification, to bridge the communication gap for the hearing-impaired. The researcher evaluated multiple methodologies and datasets used in previous studies, which consisted of diverse sign language systems like ASL and ISL.

The results showed that deep learning methods, specifically CNNs, attained superior performance in gesture recognition compared to traditional feature-based approaches.

Paper	Years	Strong	Limitations	Datasets	The Best models	Results
[1]	2025	attained a near-perfect accuracy of 99.97%	focused only on static images	ASL Alphabet	Hybrid Transformer-CNN model emerged	accuracy = 99.97%
[2]	2022	high efficiency in handling complex images	required high computational power	ArSL2018 dataset	EfficientNetB4 model	accuracy = 95%
[3]	2024	model integrated advanced feature extraction	required a large volume of training data	ASL	2D Deep CNN	high accuracy in practical
[4]	2021	Model integrated a pre-processing filter that improved the accuracy	focused mainly on static fingerspelling	ASL Alphabet	Convolutional Neural Network (CNN)	accuracy = 95.8%
[5]	2024	achieved high-quality image reconstruction	required significant computational overhead	ASL Alphabet	Semantic-based Deep Learning model	accuracy = 99%
[6]	2020	provided a detailed taxonomy of recognition phases.	complex backgrounds still posed challenges for many systems.	including ASL, ISL, and TSL datasets	Convolutional Neural Networks and Hidden Markov Models	higher accuracy and robustness in real-world scenarios.

References

- [1] Aly, Mohammed, and Islam S. Fathi. "Recognizing American Sign Language gestures efficiently and accurately using a hybrid transformer model." *Scientific Reports* 15.1 (2025): 20253.
- [2] Zakariah, Mohammed, et al. "Sign language recognition for Arabic alphabets using transfer learning technique." *Computational Intelligence and Neuroscience* 2022 (2022): 4567989.
- [3] Zhidebayeva, Aziza, et al. "Real-time sign language fingerspelling recognition system using 2D deep CNN with two-stream feature extraction approach." *International Journal of Advanced Computer Science and Applications* 15.9 (2024).
- [4] Yadav, B. K., & Bohra, H. "Sign Language to Text and Speech Conversion." *International Journal of Advance Research, Ideas and Innovations in Technology (IJARIIT)* 7.3 (2021): V713-1560.
- [5] Kouvakis, V., Trevlakakis, S. E., & Boulogeorgos, A. A. A. "Semantic Communications for Image-Based Sign Language Transmission." *IEEE Open Journal of the Communications Society* 5 (2024): 1083-1100. [5] Zhidebayeva, Aziza, et al. "Real-time sign language fingerspelling recognition system using 2D deep CNN with two-stream feature extraction approach." *International Journal of Advanced Computer Science and Applications* 15.9 (2024).
- [6] Sharma, Sakshi. "Vision-based sign language recognition system: A Comprehensive Review." *Proceedings of the Fifth International Conference on Inventive Computation Technologies (ICICT)* (2020): 978-1-7281-4685-0.



An Artificial Intelligence-Based Real-Time Sign Language Recognition System Using Convolutional Neural Networks with Linguistic Correction for the Deaf and Mute

Prepared By

Name: Anas Abdulkader Alzain

ID No.:453001724

Name: Mohammed Omar Alqathmi

ID No.:253001437

Submitted in fulfillment of the requirements for the degree Master of
Science in Artificial Intelligence

At

Collage of Informatics

Midocean University

Supervisor Name: DR. Hagar Salah

Collage of Informatics, Midocean University, Comoros

Email:.....

Acknowledgements

We would like to express our deepest appreciation and sincere gratitude to our esteemed supervisor, Dr. Hager Saleh for her exceptional guidance, continuous support, and invaluable mentorship throughout the development and completion of this Master's thesis in Artificial Intelligence.

Her profound knowledge, insightful observations, and constructive criticism have significantly enhanced the quality and rigor of this research. Her dedication to academic excellence and her commitment to our intellectual growth have been a constant source of motivation and inspiration.

Without the grace of Allah and her wise supervision and insightful guidance, this thesis would not have attained its present form. We are truly indebted to her for her patience, encouragement, and unwavering support at every stage of this academic journey.

We extend our heartfelt thanks for her time, effort, and trust in our abilities.

Abstract

Communication remains a significant barrier for the Deaf and Mute (D&M) community, particularly in interactions with the hearing majority who often lack sign language proficiency. While American Sign Language (ASL) is a primary mode of expression, traditional interpretation services are often inaccessible due to high costs and limited availability. This research proposes an automated, hardware-free, web-based fingerspelling recognition system designed to bridge this gap.

Unlike previous hardware-dependent solutions, the proposed system utilizes a standard webcam to capture live video feeds directly within a web browser. The core architecture leverages a Convolutional Neural Network (CNN) for the classification of the 26 ASL alphabet letters. To address the challenges of real-world environments, such as motion blur and background noise, a two-stage refinement process is implemented: a Re-classification logic that ensures gesture stability before output, and a Spell-check and Text-conversion module that corrects linguistic errors in the generated text.

List of Publications

[1][ijaerv13n9_90.pdf \(ripublication.com\)](#)

[2][Translation of Sign Language Finger-Spelling to Text using Image Processing \(ijcaonline.org\)](#)

[3][Sign Language to Text and Speech Conversion \(ijariit.com\)](#)

[4][Sign Language to Text and Speech Translation in Real Time Using Convolutional Neural Network – IJERT](#)

[5][\(PDF\) Conversion of Sign Language To Text And Speech Using Machine Learning Techniques \(researchgate.net\)](#)

[6] [An Improved Hand Gesture Recognition Algorithm based on image contours to Identify the American Sign Language - IOPscience](#)

Table of Contents

Chapter 1: Introduction

1.1: Overview	6
1.2 Problem Definition	7
1.3 Thesis Objectives	8
1.4 Thesis Contribution	8

Chapter 2: Related Work

2.1 Introduction	9
2.2 The Evolution of Capture Technologie.....	9
2.3 Deep Learning and CNN Architectures.....	10
2.4 Critical Analysis and Research Gaps	10

Chapter 3: Proposed Approach

3.1 Introduction	11
3.2 System Architecture and Workflow.....	11
3.3 Phase I: Data Acquisition & Preprocessing.....	12
3.4 Phase II: CNN-Based Feature Extraction & Classification.....	12
3.5 Phase III: The Re-classification Logic (Stability Control)	13
3.6 Phase IV: Linguistic Integration (Post-Processing).....	14
3.7 Phase V: Web Deployment Architecture.....	14

Chapter 4: Conclusion and Future Work

4.1 Conclusion	15
4.2 Limitations	15
4.3 Future Work	16

References	17
------------------	----

List of Abbreviations

- **Acc:** Accuracy
- **AI:** Artificial Intelligence
- **ANN:** Artificial Neural Network
- **API:** Application Programming Interface
- **ASL:** American Sign Language
- **AUC:** Area Under the Curve
- **CNN:** Convolutional Neural Network
- **CPU:** Central Processing Unit
- **CV:** Computer Vision
- **D&M:** Deaf and Mute
- **DL:** Deep Learning
- **GPU:** Graphics Processing Unit
- **JS:** JavaScript
- **NLP:** Natural Language Processing
- **ReLU:** Rectified Linear Unit
- **RGB:** Red, Green, Blue (Color Model)
- **ROC:** Receiver Operating Characteristic
- **ROI:** Region of Interest
- **SVM:** Support Vector Machine

List of Figures


1.1 recognize Fingerspelling	6
3.2 System Architecture	11

Chapter 1: Introduction

1.1 Overview

Sign language is one of the most natural and oldest forms of human communication, as it is based on visual signs made up of hand shapes, movement, facial expression, and body position. In the case of Deaf and Mute(D&M) people also known as Deaf community, the biggest problem in being successfully involved with the hearing world is not a cognitive/intellectual problem but a communication problem. Since most of the community are not able to access the spoken language, the first and primary form of communication for them is sign language.

American Sign Language (ASL) is one of the most popular sign languages in the world, second only to the spoken English language in America or even in parts of Canada. ASL consists of a very large vocabulary of signs for words and concepts, along with a fingerspelling sub-system through which each of the 26 letters of the English alphabet can be produced by a unique static or semi-static hand gesture. Fingerspelling is a common method in signed language interpretation and has many applications wherever there are proper names, technical terms, initialized signs, or no sign available for a particular word; hence, accurate recognition of the letters is critical for complete interpretation from ASL.



However, sign language is often unknown to those who can hear. Professional Interpreters professional humanity interpreters are limited, expensive, and nonviable on demand or for private events such as education, health care, work force , civil services or social life to daily. This information barrier leads to social isolation, lack of access to information, and disparity of opportunity for Deaf people.

Recent advances in computer vision, deep learning, and CNNs have made it possible to leverage an automated vision-based gesture recognition systems. These systems can record hand movements through standard cameras (such as webcams), process them in real time and translate into readable text, or even synthetic speech. The system presented here is specifically designed for the real-time recognition of fingerspelling (or manual alphabet) of ASL letters.

1.2 Problem Definition

Deaf and Mute people rely solely on visual- gestural communication using sign language, as any auditory and speech-based form of communication is not feasible. Non-verbal communication using gestures, especially hand gestures in fingerspelling, is visually interpreted, but the knowledge of sign language is not prevalent in the general population.

This creates a large gap and thus poses substantial difficulties: - The lack of effective real-time communication in real-life situations. The sole reliance on very rare and costly professional interpreters. Difficulties in education, doctor-patient communication, legal discussions, office communication, and social interactions. Manual systems are not scalable.

Early automated gesture recognition systems (such as rule-based systems or conventional machine learning using hand-designed features such as Histogram of Oriented Gradients or skin color detection) may have had difficulties in coping with real-life variability, such as variations in lighting conditions, complexity of the background, skin color, hand orientation, camera position, and motion blur.

A reliable and real-time system is thus needed:

one that can process live camera feed, properly segment the hand, classify fingerspelled letters with high accuracy, and perform under real-life constraints such as low latency and commodity hardware.

The central problem addressed in this thesis is the design of an effective CNN-based system that can recognize the 26 ASL alphabet letters in real time with a negligible margin of error, thus enabling easier human-computer interaction for the Deaf.

1.3 Thesis Objectives

The overall objective of this thesis is to develop and test a real-time fingerspelling recognition system for the ASL alphabet using convolutional neural networks. The objectives are:

- To develop an efficient preprocessing system for automatically locating and isolating the hand region from images captured using a webcam, and to remove the impact of environmental changes (lighting, background, etc.).
- To develop and train a CNN classifier for optimal recognition of the 26 different ASL letter gestures with high accuracy.
- To ensure real-time processing capabilities for real-time video streams, with minimal latency.
- To incorporate post-processing techniques (spell checking, etc.) for improving the letter sequences into readable text output.

1.4 Thesis Contribution

The following are the key contributions made

Comprehensive Recognition System:

- Development of a comprehensive system that encompasses image processing, deep learning, and linguistic post-processing.

Intelligent Correction Layer:

- The addition of a "Spell Check" module, which enhances the system from a simple character recognition system to a working communication system.

Improved Accuracy through Re-classification:

- The addition of a feedback mechanism in the CNN classification step to handle high-uncertainty gestures.

Scalable Social Impact:

- Development of a low-latency and low-cost system that requires minimal human interaction, providing equal access to the D&M community.

Chapter 2: Related Work

2.1 Introduction

The Sign Language Recognition (SLR) community has witnessed a paradigm shift from intrusive hardware solutions to seamless vision-based software solutions. This chapter presents an overview of the literature, dividing the existing work into hardware dependencies, traditional machine learning, and the current trend of Deep Learning.

Emphasis is placed on the rise of web-based solutions and the current challenges in real-time linguistic processing.

2.2 The Evolution of Capture Technologies

2.2.1 Sensor-Based Frameworks

Traditionally, the most popular approach to hand gesture recognition involved the use of "Data Gloves" and body sensors. These sensors measured joint angles and coordinates with high accuracy. However, as has been stated in many existing works, these systems were plagued by severe "User Friction." The need to wear costly, hardware-attached sensors made it impossible for the Deaf and Mute (D&M) community to employ these tools in natural, real-world settings. This led to the need for "Contactless" systems that employ common optical sensors (webcams).

2.2.2 Vision-Based Traditional Methods

The shift to computer vision began with "Hand-Crafted Feature Extraction." Researchers employed algorithms such as SIFT (Scale-Invariant Feature Transform) and HOG (Histogram of Oriented Gradients) to detect hand shapes. Although these systems were an improvement over their predecessors in terms of usability, they were extremely prone to "Environmental Noise." Even a slight variation in lighting conditions or a complex background resulted

in a complete system breakdown. This highlighted the need for more flexible architecture that could "learn" features rather than relying on software-defined ones.

2.3 Deep Learning and CNN Architectures

The use of Convolutional Neural Networks (CNNs) has brought about a paradigm shift in the field by allowing for the automation of feature extraction. Feature Hierarchy:

CNNs have been shown to be particularly adept at learning a hierarchy of features, ranging from simple edges to complex finger orientations.

This is particularly useful for American Sign Language (ASL), where the difference between two letters can be as subtle as the position of a thumb.

Generalization:

Unlike traditional approaches, deep learning models trained on a variety of datasets have been shown to generalize better across different skin tones and hand shapes, making them more amenable to a worldwide audience.

2.4 Critical Analysis and Research Gaps

Despite the high performance of modern CNNs in the lab, two specific research gaps remain widespread in the literature, and are addressed by this proposed research:

2.4.1 The Persistence of Visual Ambiguity

Most existing systems are based on a "Single-Frame Prediction" paradigm. In a real-time webcam stream, the presence of motion blur or improper hand placement may result in the system producing a high-frequency oscillation of incorrect letters.

There is a recorded absence of Iterative Verification (or Re-classification) logic in most existing systems, which is required to guarantee the stability of the output prior to its display to the user.

2.4.2 The Linguistic Integration Gap

One of the key shortcomings identified in most existing SLR projects is that they are purely "Pattern Recognizers" and not "Communication Tools." They produce raw character data that fail to factor in human error or spelling

mistakes. Scholarly literature has pointed out that for an SLR system to be truly useful, it needs to implement a Post-Processing Layer.

The implementation of Spell-Checking and Text Conversion algorithms is a crucial but often overlooked step in forming a seamless link between gestural input and meaningful text.

Chapter 3: Proposed Approach (Methodology)


3.1 Introduction

The methodology of this research aims to develop a strong and complete end-to-end framework for real-time recognition of American Sign Language (ASL). The proposed framework is more than a classifier; it is a complete communication system running on a web-based platform. In this chapter, the system architecture will be described in detail, from the raw webcam feed to the final linguistic correction and display.

3.2 System Architecture and Workflow

The system architecture is a sequential yet iterative process aimed at achieving the highest accuracy while maintaining the lowest latency possible for real-time communication. The system workflow is broken down into four major domains:

- Optical Acquisition and Signal Preprocessing.
- Neural Network Classification Engine.
- Ambiguity Management (Re-classification Logic).
- Linguistic Correction and Textual Synthesis.



3.3 Phase I: Data Acquisition & Preprocessing

The first phase of the system is of utmost importance, as the quality of the input data directly affects the performance of the neural network engine.

3.3.1 Webcam Input Stream

The system uses a standard RGB webcam for live video capture. Unlike depth cameras, where the challenge is to capture three-dimensional data, the challenge in this case is to capture useful information from a two-dimensional plane. The video is captured at a standard rate (e.g., 30 FPS) and processed frame by frame.

3.3.2 Image Filtering and Noise Reduction

To make the system environment-independent, several preprocessing filters are applied:

Grayscale Conversion / Color Normalization: To simplify computations and eliminate the effects of skin tones and room lighting.

Gaussian Blurring: Used to blur the image and eliminate "salt-and-pepper" noise that might otherwise mislead the CNN layers.

ROI (Region of Interest) Extraction: The system extracts and crops the region of interest containing the hand, thus eliminating unnecessary background information (such as furniture or other people).

3.4 Phase II: CNN-Based Feature Extraction & Classification

This phase is the heart of the computational engine of the project, where visual information is converted into alphanumeric character predictions.

3.4.1 Dataset Storage and Preparation

A large dataset of thousands of images for each of the 26 letters of the ASL alphabet is used. This dataset is "augmented" (using methods such as rotation, zooming, and translation) to train the model to recognize signs regardless of whether the hand is centered or rotated.

3.4.2 Convolutional Neural Network (CNN) Architecture

The system uses a deep CNN to automatically learn the spatial hierarchy of hand gestures. The architecture includes:

- Convolutional Layers: These layers use specific filters (kernels) to identify low-level features (edges and curves) and high-level features (finger positions and thumb placement).
- Activation Functions (ReLU): To add non-linearity to the model, enabling it to identify complex patterns in the gestures.
- Pooling Layers (Max Pooling): To reduce the spatial dimensions of the data, making the system faster and more focused on the most dominant features of the gesture.
- Fully Connected (Dense) Layers: The final layers that combine all the learned features to predict the probability of each of the 26 letters.

3.5 Phase III: The Re-classification Logic (Stability Control)

One of the main innovations in this project is the re-classification mechanism. In a live webcam feed, a user's hand may move or blur, resulting in the model providing a "flickering" output.

3.5.1 Thresholding and Verification

- Rather than showing all the predicted letters immediately, the system uses
- verification logic:
- Probability Check: The system checks the confidence level of the CNN. If the confidence level is less than a certain threshold (e.g., 85%), the gesture is marked as "ambiguous."
- Temporal Consistency: The system waits for the same letter to appear in multiple consecutive frames (e.g., 5 frames) before accepting the input.
- Feedback Loop: When a gesture is marked as unstable, the system initiates a "Re-classification" request, asking the engine to re-examine the hand area until a stable, confident prediction is reached.

3.6 Phase IV: Linguistic Integration (Post-Processing)

A character-by-character output is hard to interpret for hearing-impaired people. This phase translates raw "letters" into "language."

3.6.1 Text Conversion and Buffer Management

As the letters are verified by the re-classification logic, they are retained in a temporary buffer. The system identifies pauses (silent intervals) to identify when a word has been finished.

3.6.2 Spell Check and Error Correction

As human signing may be error-prone, and model classification may occasionally go wrong, a Spell Check Module is incorporated:

- **Dictionary Mapping:** The system checks the generated word against a dictionary of common English words.
- **Levenstein Distance Algorithm:** When a word is not identified (e.g., "H-E-L-M-O"), the system identifies the closest valid word ("H-E-L-L-O") and proposes or automatically implements the correction.

3.6.3 Output Display

The final, corrected word is displayed on the Website Interface. This enables a clean, user-friendly text display that allows a smooth conversation between the D&M signer and the hearing observer.

3.7 Phase V: Web Deployment Architecture

The entire process is engineered for a browser-based platform:

- **Client-Side Processing:** With the use of optimized models, most of the image processing is done on the user's browser, ensuring privacy and lower server expenses.
- **Interface Design:** The website is designed to be minimalist, featuring a large camera view and a prominent text-output box for optimal accessibility.

Chapter 4: Conclusion and Future Work

4.1 Conclusion

The study described in this proposal addresses one of the most significant challenges in human communication: narrowing the gap between the Deaf and Mute (D&M) community and the hearing majority. By leveraging Deep Learning and modern Web Technologies, a hardware-free, accessible, and intelligent system for American Sign Language (ASL) recognition has been developed.

The strength of this research lies in its integrated pipeline. Unlike conventional models that focus only on gesture classification, the proposed system incorporates an advanced Re-classification mechanism to manage the instability of live video streams, along with a Linguistic Spell-Check module to enhance the accuracy of the final output. Through high-precision classification using Convolutional Neural Networks (CNNs) and full deployment as a browser-based application, the project makes assistive technology widely accessible to anyone with a webcam and internet browser. Ultimately, this work demonstrates that artificial intelligence can function as a seamless, real-time bridge for social inclusion and equitable communication.

4.2 Limitations

Although the proposed framework offers a reliable solution for ASL fingerspelling recognition, certain limitations must be acknowledged to maintain academic transparency:

- **Static Nature of Fingerspelling:** The current implementation is restricted to the 26 static letters of the ASL alphabet. Dynamic signs involving complex temporal hand movements are not yet supported.
- **Environmental Extremes:** Despite the use of preprocessing techniques, extremely low-light environments or highly cluttered backgrounds especially those containing skin-toned objects may still affect segmentation accuracy.
- **Linguistic Depth:** The spell-check module is optimized for general English vocabulary. However, it may encounter difficulties when processing highly specialized terminology in domains such as medicine or law without further expansion of the lexical database.

4.3 Future Work

The framework established in this research provides a scalable foundation for continued advancements in assistive computer vision. Several future directions are proposed:

4.3.1 Transition to Dynamic Sign Recognition

A logical progression of this work involves extending the CNN model into hybrid architecture, such as CNN-LSTM (Long Short-Term Memory) networks or Transformer-based models. This enhancement would enable the recognition of dynamic, motion-based signs and complete sentences by capturing the temporal dynamics of natural sign language.

4.3.2 Mobile and Edge Optimization

Future improvements will focus on optimizing the model for Edge Devices. This includes developing dedicated mobile applications and Progressive Web Apps (PWAs) capable of offline operation, ensuring accessibility even in areas with limited internet connectivity.

4.3.3 Multi-Language Support

Expanding the platform to accommodate additional sign languages—such as Arabic Sign Language or British Sign Language would significantly broaden its global reach and promote inclusion on an international scale.

4.3.4 Integration of Emotion Recognition

Incorporating facial expression analysis into the recognition pipeline would allow the system to interpret not only the lexical content of signs but also the associated emotional tone. This would result in a more comprehensive and nuanced understanding of user intent, further enhancing communication accuracy.

References

[1]

<https://www.springerprofessional.de/en/sign-language-to-text-conversion-using-deep-learning/18414190>

[2]

<https://www.slideshare.net/slideshow/real-time-conversion-of-sign-language-to-text-and-speech-presentation/259563157>

[3]

<https://www.signfordeaf.com/>

[4]

<https://ieeexplore.ieee.org/document/9996001/>